

INDUSTRIAL COMPONENT DATA

EASY800-BLT-ADP 167651 EATON ELECTRIC Bluetooth Adapter, communication easy800/MFD-CP8/CP10/EC4P with PC, pl..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY800-BLT-ADP



Manufacturer	EATON - MOELLER
MPN / Reference	EASY800-BLT-ADP
Catalog number	167651
Category	PLC communication module
Minimum order	1 Pcs
Document ID	EO-4D21B15B05
Generated	2026-08-03

Product Overview

Bluetooth Adapter, communication easy800/MFD-CP8/CP10/EC4P with PC, plug-in

Bluetooth adapter module; For Easy800, MFD-CP8/CP10, EC4P

Bluetooth adapter for radio connection between the PC and 800 IEC8-10-4, V2.0 EDR conform, 4 dBm, PIN code-based secure connection, range approx. 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > EASY programmable relays and MFD displays**

Additional Product Information

Bluetooth Adapter, communication easy800/MFD-CP8/CP10/EC4P with PC, plug-in Bluetooth adapter for radio connection between the PC and 800 IEC8-10-4, V2.0 EDR conform, 4 dBm, PIN code-based secure connection, range approx. 10 m

Delivery program

Product range Control relay easyRelay

Multi-function-display MFD-Titan Subrange Programming accessories

Cables, component adapters and plugs Function For secure radio connection between control relay and PC (programming and online communication)/Android smartphone and tablet (easyRemote display app, easyParameter app) For use with easy81..., easy82...

MFD-CP8, MFD-CP10 ? V. 3.0

EC4P radio interface Bluetooth module used easy800-BLT-ADP 02, 03: PAN1321 SPP, ENW89811K4CF

easy800-BLT-ADP 04: PAN1322 SPP, ENW89841A3KF BlueTooth [Version] 2.0, EDR conform Transmitting powerOutput level typ. 2.5 mW Transmitting powerOutput power typ. 4 dBm Transmitting powerClass 2 Transmitting powerTransission mode easy800-BLT-ADP 02, 03 secure connection using PIN code
easy800-BLT-ADP 04 secure connection using secure simple pairing Transmitting powerBaud rate 57600 Bd Transmitting powerRange 10 m Communications partners [Count] max. 4 Communications partners [Type] PC Technical data
General Standards EN 55011, EN 50178, IEC EN 61000-4, IEC60068-2-6, IEC60068-2-27 Dimensions (W x H x D) 15 x 45 x 17 mm Weight 0.08 kg Mounting Can be plugged into the easy800-Standard, MFD-CP8/CP10, EC4P serial interface
Climatic proofing Cold to EN 60068-2-1
Heat to IEC 600...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY800-BLT-ADP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.