

INDUSTRIAL COMPONENT DATA

+NZM2-250-XKCU 262243 Y7-262243 EATON ELECTRIC Box terminal, 3p, bottom up to 300A. Can only be sold assembl..

Brand: EATON - MOELLER | Manufacturer Part Number: +NZM2-250-XKCU



Manufacturer	EATON - MOELLER
MPN / Reference	+NZM2-250-XKCU
Catalog number	Y7-262243
Category	Wiring set for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-4DACBC13D2
Generated	2026-08-05

Product Overview

Box terminal, 3p, bottom up to 300A. Can only be sold assembled.

+NZM2-250-XKCU

Box terminal, 3p, bottom up to 300A

Optional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple. Notes: part no. suffix and part no. contain parts for a circuit-breaker side at top or bottom for 3 or 4 pole circuit-breakers. Conversion kit for circuit-breaker with screw connection. Fitted within the switch housing. O = for fitting at the top. U = for fitting at the bottom. U e ? 525 VAC. Use cover NZM2(-4)-XKSA. Use ferrules with flexible and highly flexible conductors . Max. cross section shown can only be connected when flexible and without ferrules. Can be used for: NZM2(-4), PN2(-4), N(N/O)2(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Box terminal, 3p, bottom up to 300AOptional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple. Notes: part no. suffix and part no. contain parts for a circuit-breaker side at top or bottom for 3 or 4 pole circuit-breakers. Conversion kit for circuit-breaker with screw connection. Fitted within the switch housing. O = for fitting at the top. U = for fitting at the bottom. U e ? 525 VAC. Use cover NZM2(-4)-XKSA. Use ferrules with flexible and highly flexible conductors . Max. cross section shown can only be connected when flexible and without ferrules. Can be used for: NZM2(-4), PN2(-4), N(N/O)2(-4)

General specificationsProduct nameEaton Moeller series NZM connection typePart

no.+NZM2-250-XKCUEAN4015082622435Product Length/Depth103 millimetreProduct height184 millimetreProduct width105 millimetreProduct weight0.077 kilogramCompliancesIEC
RoHS conformProduct TradenameNZMProduct TypeAccessoriesProduct Sub TypeConnection typeDelivery programTypeAccessoryBox terminalTerminalNumber of polesThree-poleAmperage Rating? 300 AFrameNZM2Suitable forThree-pole
Copper cableUsed withNZM2(-4), PN2(-4), N(S)2(-4)Technical Data - MechanicalMounting positionFitted at the bottomTechnical Data - Mechanical - TerminalsTerminal capacity (stranded cable)4 mm² - 70 mm² (2x)
Up to 95 mm² can be connected depending on the cable manufacturer.
12 - 350 AWG/kcmil (1x)
10 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +NZM2-250-XKCU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.