

INDUSTRIAL COMPONENT DATA

+NZM3-XKCU 262245 Y7-262245 EATON ELECTRIC Box terminal, 3p, bottom up to 630A. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +NZM3-XKCU



Manufacturer	EATON - MOELLER
MPN / Reference	+NZM3-XKCU
Catalog number	Y7-262245
Category	Wiring set for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-6802DCD956
Generated	2026-08-04

Product Overview

Box terminal, 3p, bottom up to 630A. Can only be sold assembled.

+NZM3-XKCU

Box terminal, 3p, bottom up to 630A

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: part no. suffix and part no. contain parts for a circuit-breaker side at top or bottom for 3 or 4 pole circuit-breakers. Conversion kit for circuit-breaker with screw connection. Fitted within the switch housing. O = for fitting at the top. U = for fitting at the bottom. U e ? 525 VAC. use NZM3(-4)-XKSA cover. Use ferrules with flexible and highly flexible conductors., observe limited terminal capacity through sleeve . Can be used for: NZM3(-4), PN3(-4), N(N/O)3(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Box terminal, 3p, bottom up to 630AOptional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: part no. suffix and part no. contain parts for a circuit-breaker side at top or bottom for 3 or 4 pole circuit-breakers. Conversion kit for circuit-breaker with screw connection. Fitted within the switch housing. O = for fitting at the top. U = for fitting at the bottom. U e ? 525 VAC. use NZM3(-4)-XKSA cover. Use ferrules with flexible and highly flexible conductors., observe limited terminal capacity through sleeve . Can be used for: NZM3(-4), PN3(-4), N(N/O)3(-4)

General specificationsProduct nameEaton Moeller series NZM - Molded Case Circuit BreakerPart

no.+NZM3-XKCU EAN4015082622459 Product Length/Depth 120.5 millimetre Product height 275 millimetre Product width 140 millimetre Product weight 0.134 kilogram

Compliances

UL/CSA IEC

RoHS conform

Certifications

UL (Category Control Number DIHS)

UL listed

UL489

CSA (File No. 22086)

IEC60947

CSA certified

UL (File No. E31593)

CE marking

CSA-C22.2 No. 5-09 Product Trade name NZM Product Type Molded Case Circuit Breaker Product Sub Type None Delivery program Type Accessory Box terminal Terminal Number of poles Three-pole Amperage Rating? 630 A Frame NZM3 Suitable for Copper cable

Three-pole Used with NZM3(-4), PN3(-4), N(S)3(-4) Technical Data - Mechanical Mounting position Fitted at the bottom Technical Data - Mech...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +NZM3-XKCU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.