

INDUSTRIAL COMPONENT DATA

+NZM3-XKCO 262246 Y7-262246 EATON ELECTRIC Box terminal, 3p, top to 630A. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +NZM3-XKCO



Manufacturer	EATON - MOELLER
MPN / Reference	+NZM3-XKCO
Catalog number	Y7-262246
Category	Wiring set for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-033385F164
Generated	2026-08-03

Product Overview

Box terminal, 3p, top to 630A. Can only be sold assembled.

+NZM3-XKCO

Box terminal, 3p, top to 630A

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: part no. suffix and part no. contain parts for a circuit-breaker side at top or bottom for 3 or 4 pole circuit-breakers. Conversion kit for circuit-breaker with screw connection. Fitted within the switch housing. O = for fitting at the top. U = for fitting at the bottom. U e ? 525 VAC. use NZM3(-4)-XKSA cover. Use ferrules with flexible and highly flexible conductors., observe limited terminal capacity through sleeve . Can be used for: NZM3(-4), PN3(-4), N(N/O)3(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Box terminal, 3p, top to 630AOptional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: part no. suffix and part no. contain parts for a circuit-breaker side at top or bottom for 3 or 4 pole circuit-breakers. Conversion kit for circuit-breaker with screw connection. Fitted within the switch housing. O = for fitting at the top. U = for fitting at the bottom. U e ? 525 VAC. use NZM3(-4)-XKSA cover. Use ferrules with flexible and highly flexible conductors., observe limited terminal capacity through sleeve . Can be used for: NZM3(-4), PN3(-4), N(N/O)3(-4)

General specificationsProduct nameEaton Moeller series NZM connection typePart

no.+NZM3-XKCOEAN4015082622466Product Length/Depth120.5 millimetreProduct height275 millimetreProduct width140 millimetreProduct weight0.134 kilogramCompliancesIEC

UL/CSA

RoHS conformCertificationsUL (Category Control Number DIHS)

CSA (Class No. 1437-01)

CSA (File No. 22086)

CE marking

UL listed

UL (File No. E31593)

IEC60947

CSA-C22.2 No. 5-09

UL489

CSA certifiedProduct TradenameNZMProduct TypeAccessoriesProduct Sub TypeConnection typeDelivery programTypeAccessoryBox terminalTerminalNumber of polesThree-poleAmperage Rating? 630 AFrameNZM3Suitable forThree-pole

Copper cableUsed withNZM3(-4), PN3(-4), N(S)3(-4)Technical Data - MechanicalMounting positionFitted aboveTechnical Data - Mechanical -....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +NZM3-XKCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.