

INDUSTRIAL COMPONENT DATA

+NZM2-4-250-XKCO 266752 Y7-266752 EATON ELECTRIC Box terminal, 4p, top to 300A. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +NZM2-4-250-XKCO



Manufacturer	EATON - MOELLER
MPN / Reference	+NZM2-4-250-XKCO
Catalog number	Y7-266752
Category	Wiring set for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-E09206CD9A
Generated	2026-08-04

Product Overview

Box terminal, 4p, top to 300A. Can only be sold assembled.

+NZM2-4-250-XKCO

Eaton Moeller series NZM - Molded Case Circuit Breaker. Box terminal, 4p, top to 300A

Optional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple. Notes: part no. suffix and part no. contain parts for a circuit-breaker side at top or bottom for 3 or 4 pole circuit-breakers. Conversion kit for circuit-breaker with screw connection. Fitted within the switch housing. O = for fitting at the top. U = for fitting at the bottom. U e ? 525 VAC. Use cover NZM2(-4)-XKSA. Use ferrules with flexible and highly flexible conductors . Max. cross section shown can only be connected when flexible and without ferrules. Can be used for: NZM2(-4), PN2(-4), N(N/O)2(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM connection type Catalog Number 266752 Model Code +NZM2-4-250-XKCO EAN 4015082667528 Product Length/Depth 75 mm Product Height 25 mm Product Width 75 mm Product Weight 0.076 kg

Compliances IEC

RoHS conform Product specifications

Terminal capacity (stranded cable) 12 - 350 AWG/kcmil (1x)

Up to 95 mm² can be connected depending on the cable manufacturer.

4 mm² - 70 mm² (2x)

10 mm² - 185 mm² (1x) 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. Frame NZM2 10.4 Clearances and creepage distances Meets the product standard's requirements.

Suitable for Four-pole

Copper cable 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. Amperage Rating ? 300 A 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. Terminal capacity (copper strip) 2 segments of 9 mm x 0.8 mm - 10 segments of 16 mm x 0.8 mm or 8 segments of 15.5 mm x 0.8 mm (2x) 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.8 Connections for external conductors Is the panel builder's responsibility.....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +NZM2-4-250-XKCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.