

INDUSTRIAL COMPONENT DATA

BPZ-KB-24/250 289971 Y7-289971 EATON ELECTRIC Block distributor 250A/63A

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-KB-24/250



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-KB-24/250
Catalog number	Y7-289971
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-C2DA10A5F5
Generated	2026-08-05

Product Overview

Block distributor 250A/63A

BPZ-KB-24/250

Eaton xEnergy Basic LV systems Low voltage switchgear. Terminal block, 250 A/63 A

4-phase busbar, BPZ-KB-24/250, 12 outgoers per pole, neutral conductor 24 outgoers, 250 A busbar for powering a series of module devices, max. rated operational current per outgoer is 63 A, every plug closes automatically, ensuring a high level of safety. No direct contact risk, as per IP20, L x W x H: 427mm x 40mm x 50mm, equipment supplied: 1 4-phase busbars

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic other accessory Catalog Number 289971 Model Code BPZ-KB-24/250 EAN 4015082899714 Product Length/Depth 51 mm Product Height 84 mm Product Width 427 mm Product Weight 1.3 kg

Compliances RoHS conform Delivery program

Amperage rating 250 A Number of poles Four-pole Technical data - mechanical

Mounting method Flush mounting

Surface mounting

Floor standing distribution board Mounting position Universal Number of clamp positions per pole 12 Number of clamping units per pole 12 Conductor cross section (flexible, fine-strand) with cable end sleeve - min 1.5 mm² Conductor cross section (flexible, fine-strand) with cable end sleeve - max 10 mm² Conductor cross section (solid, solid-strand) - min 0 mm²

Conductor cross section (solid, solid-strand) - max 0 mm² Additional information

Fitted with: N-rail Functions Additional equipment

ETIM for 289971 Power distribution systems (EC001894)

Feature Name

Feature Value

Height (EF000040)

84 mm

Width (EF000008)

427 mm

Depth (EF000049)

51 mm

Max. rated current (EF007926)

250 A

Number of poles (EF001391)

4

Conductor cross section flexible (fine-strand) with cable end sleeve (EF003460)

1.5 mm²

Conductor cross section solid (solid, stranded) (EF003462)

0 mm²

Number of clamp positions per pole (EF002519)

12

With PE-rail (EF007967)

No

With N-rail (EF007963)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-KB-24/250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.