

INDUSTRIAL COMPONENT DATA

DX-BR006-33K3 171902 Y7-171902 EATON ELECTRIC 171902 DX-BR006-33K3

Brand: EATON - MOELLER | Manufacturer Part Number: DX-BR006-33K3



Manufacturer	EATON - MOELLER
MPN / Reference	DX-BR006-33K3
Catalog number	Y7-171902
Category	Accessories/spare parts for frequency controller
Minimum order	1 Pcs
Document ID	EO-19BEB59E3B
Generated	2026-08-05

Product Overview

171902 DX-BR006-33K3

DX-BR006-33K3

Braking resistance, IP20, 6 ?, 33.3 kW, For use with: DC1, DA1, DL1, DG1, SVX, SPX

Braking resistance, Description: Steel grid resistor, combined, Installed in a housing designed to prevent accidental contact and featuring a temperature monitoring switch and internal connection terminals/terminal bolts, For use with: DC1, DA1, DL1, DG1, SVX, SPX, Continuous braking rating: PDB= 33.3 kW

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Power XL Frequency Converters**

Additional Product Information

Braking resistance, IP20, 6 ?, 33.3 kW, For use with: DC1, DA1, DL1, DG1, SVX, SPXBraking resistance, Description: Steel grid resistor, combined, Installed in a housing designed to prevent accidental contact and featuring a temperature monitoring switch and internal connection terminals/terminal bolts, For use with: DC1, DA1, DL1, DG1, SVX, SPX, Continuous braking rating: PDB= 33.3 kW

General specificationsProduct nameEaton DX Braking resistorPart no.DX-BR006-33K3EAN4015081684021Product Length/Depth1200 millimetreProduct height450 millimetreProduct width800 millimetreProduct weight85

kilogramCertificationsC22.2

UL report applies to both US and Canada

UL

UL Category Control No.: NMTR2, NMTR8

Certified by UL for use in Canada

UL508

UL File No.: E300273Product TradenameDXProduct TypeAccessoryProduct Sub TypeBraking resistorCatalog

NotesInstalled in a housing designed to prevent accidental contact and featuring a temperature monitoring switch and internal connection terminals/terminal bolts

Steel grid resistor, combinedGeneral informationAccessory/spare part typeBreaking resistanceDegree of protectionIP00 IP20Product CategoryAccessoriesSuitable forBranch circuits, (UL/CSA)Used withDA1, DG1Electrical ratingVoltage rating - max1000 VDesign verification10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials to nor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DX-BR006-33K3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.