

**INDUSTRIAL COMPONENT DATA**

# EASY205-ASI 221598 0004520913 EATON ELECTRIC Bus module, AS-Interface, 24 V DC, 4DI, 4DO, addressable 0-31, ..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY205-ASI



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | EASY205-ASI     |
| Catalog number  | 0004520913      |
| Category        | Logic module    |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-8B832842D8   |
| Generated       | 2026-08-03      |

## Product Overview

Bus module, AS-Interface, 24 V DC, 4DI, 4DO, addressable 0-31, easyLink

Easy Communication Module; AS-Interface

Bus module, as AS-Interface slave, rated operating voltage 24VDC, 4 inputs, 4 outputs, 4 parameter bits addresses available 0-31, can be used via easyLink for easy700 / easy800 / MFD-CP8/CP10 / EC4P / ES4P

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > EASY programmable relays and MFD displays |
|--------------|-------------------------------------------------------------|

## Additional Product Information

EL-Nummer (Norway)4520913Bus module, AS-Interface, 24 V DC, 4DI, 4DO, addressable 0-31, easyLinkBus module, as AS-Interface slave, rated operating voltage 24VDC, 4 inputs, 4 outputs, 4 parameter bits addresses available 0-31, can be used via easyLink for easy700 / easy800 / MFD-CP8/CP10 / EC4P / ES4PDelivery program

Product rangeControl relay easyRelay

Multi-function-display MFD-TitanSubrangeBus modulesAccessoriesBus modulesBasic functionExpansionsDescriptionCan be used through easyLink

Slave

4 inputs

4 outputs

4 parameter bits

Addresses available: 0 - 31Bus protocolAS-InterfaceFor use witheasy700

easy800

EC4P

MFD-CP8..

ES4PTechnical data

General Standards EN 55011, EN 55022, IEC/EN 61000-4, IEC 62026 Dimensions (W x H x D) 35.5 x 90 x 58 (2 PE)  
mm Weight 0.07 kg Mounting Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1  
(accessories) Terminal capacities Solid 0.2/4 (AWG 22 - 12) mm<sup>2</sup> Flexible with ferrule 0.2/2.5 (AWG 22 - 12) mm<sup>2</sup> Standard  
screwdriver 0.8 x 3.5 mm Max. tightening torque 0.6 Nm Climatic environmental conditions Operating ambient temperature -25  
to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °C Condensation Take appropriate measures to prevent  
condensation Storage - 40 - 70 °C Relative humidity, non-condensing (IEC/EN 60068-2-30) 5 - 95 % Air pressure  
(operation) 795 - 1080 hPa Ambient conditions, mechanical Protection type (IEC/EN 60529, EN50178, VBG 4) IP20 Vibrations  
(IEC/EN 60068-2-6) Constant amplitude 0.15 mm 10 - 57 Hz Vibrations (IEC/EN 6006...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY205-ASI with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.