

INDUSTRIAL COMPONENT DATA

EASY204-DP 212316 0004520914 EATON ELECTRIC Bus module, PROFIBUS-DP, 24 V DC, addressable 1-126, easyLink

Brand: EATON - MOELLER | Manufacturer Part Number: EASY204-DP



Manufacturer	EATON - MOELLER
MPN / Reference	EASY204-DP
Catalog number	0004520914
Category	Logic module
Minimum order	1 Pcs
Document ID	EO-842D6F115B
Generated	2026-08-05

Product Overview

Bus module, PROFIBUS-DP, 24 V DC, addressable 1-126, easyLink

Easy Communication Module; Profibus DP

Bus module, as PROFIBUS-DP slave, rated operating voltage 24VDC, addressable 1-126, can be used via easyLink for easy700 / easy800 / MFD-CP8/CP10 / EC4P / ES4P

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

Bus module, PROFIBUS-DP, 24 V DC, addressable 1-126, easyLink Bus module, as PROFIBUS-DP slave, rated operating voltage 24VDC, addressable 1-126, can be used via easyLink for easy700 / easy800 / MFD-CP8/CP10 / EC4P / ES4P

Delivery program

Product range Control relay easyRelay

Multi-function-display MFD-Titan Subrange Bus modules Accessories Bus modules Basic function Expansions Description

Can be used through easyLink

Slave

Addresses available: 1 - 126 Bus protocol PROFIBUS-DP Supply voltage 24 V DC For use with easy700

easy800

EC4P

MFD-CP8..

ES4P Technical data

General Standards EN 55011, EN 55022, IEC/EN 61000-4, IEC 61158 Dimensions (W x H x D) 35.5 x 90 x 58 (2 PE) mm
Weight 0.15 kg Mounting Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1
(accessories) Terminal capacities Solid 0.2/4 (AWG 22 - 12) mm² Flexible with ferrule 0.2/2.5 (AWG 22 - 12) mm²
Standard screwdriver 0.8 x 3.5 mm Max. tightening torque 0.6 Nm Climatic environmental conditions Operating ambient
temperature -25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °C Condensation Take appropriate measures
to prevent condensation Storage - 40 - 70 °C Relative humidity, non-condensing (IEC/EN 60068-2-30) 5 - 95 % Air pressure
(operation) 795 - 1080 hPa Ambient conditions, mechanical Protection type (IEC/EN 60529, EN50178, VBG 4) IP20
Vibrations (IEC/EN 60068-2-6) Constant amplitude 0.15 mm 10 - 57 Hz Vibrations (IEC/EN 60068-2-6) Constant acceleration
2 g 57 - 150 Hz....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY204-DP with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.