

INDUSTRIAL COMPONENT DATA

XN-BR-24VDC-D 140071 Y7-140071 EATON ELECTRIC Bus refreshing module XI/ON, 24 V DC

Brand: EATON - MOELLER | Manufacturer Part Number: XN-BR-24VDC-D



Manufacturer	EATON - MOELLER
MPN / Reference	XN-BR-24VDC-D
Catalog number	Y7-140071
Category	Fieldbus, decentr. periphery - power supply/segment module
Minimum order	1 Pcs
Document ID	EO-59E781D35F
Generated	2026-08-02

Product Overview

Bus refreshing module XI/ON, 24 V DC

XN-BR-24VDC-D

Eaton XN Bus refreshing module XI/ON, 24 V DC

The XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Remote I / O Modules XION

Additional Product Information

General specifications

Product Name Eaton XN Bus refreshing module Catalog Number 140071 Model Code XN-BR-24VDC-D EAN

7640130120518 Product Length/Depth 55.4 mm Product Height 74.1 mm Product Width 12.6 mm Product Weight 0.037 kg

Compliances RoHS Compliant

CE Marked Certifications UL Listed

IEC/EN 61000-6-4

UL report applies to both US and Canada

UL 508

CE

Certified by UL for use in Canada

CSA Class No.: 2252-01, 2252-81

IEC/EN 61131-2

UL Category Control No.: NRAQ, NRAQ7

CULus

UL File No.: E205091

UL Recognized

CSA-C22.2 No. 142

IEC/EN 61000-6-2

IEC/EN 6113-2 Catalog Notes System power supply 24 V DC for generation of power for module bus and gateway

(XN-GW-...) Features & Functions

Electric connection type Screw-/spring clamp connection Features Fieldbus connection over separate bus coupler possible

Fitted with: Potential separation Functions Bus diagnosis possible General

Admissible range 18 - 30 V DC, Supply module Degree of protection IP20 Mounting method Rail mounting possible Product category XN Slice module Residual ripple < 5 % (according to EN 61131-2) Suitable for Base modules without

C-Connection: 2-/3-wire

Base modules with C-connection: 4-wire Suitable as Segment module Type XI/ON power supply module Used with

XN-P3T-SBB

XN-P3S-SBB

XN-P4S-SBBC-B

XN-P4S-SBBC, XN-P3T-SBB-B

XN-P4T-SBBC

XN-P4T-SBBC-B

XN-P3S-SBB-B

XN-P4S-SBBC

XN-P3T-SBB-B Voltage type DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-BR-24VDC-D with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.