

INDUSTRIAL COMPONENT DATA

SWD4-RC8-10 116020 Y7-116020 EATON ELECTRIC Bus termination, SmartWire-DT, for flat cable

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-RC8-10



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-RC8-10
Catalog number	Y7-116020
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-A1D3A57098
Generated	2026-08-05

Product Overview

Bus termination, SmartWire-DT, for flat cable

SWD4-RC8-10

Eaton SWD4 Bus termination, SmartWire-DT, for flat cable

SmartWire-DT bus termination, is plugged into the SWD ribbon cable SWD4-8MF2 on the end of the SWD flat cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Bus termination resistor Catalog Number 116020 Model Code SWD4-RC8-10 EAN 4015081157600 Product Length/Depth 10 mm Product Height 35 mm Product Width 49 mm Product Weight 0.011 kg

Certifications UL File No.: E29184

CSA

CSA Class No.: 3211-07

UL Category Control No.: NKCR

CSA File No.: 2324643

EN 50178

IEC/EN 61131-2

UL Features & Functions

Functions For the SmartWire-DT bus termination on the SmartWire-DT ribbon cable General

Current consumption 17 mA Degree of protection IP20 (according to IEC/EN 60529, EN 50178, VBG 4)

IP20 Overvoltage category II Pollution degree 2 Product category SmartWire-DT accessories Type SmartWire-DT bus termination; plugged onto SWD4-8MF2 blade terminal at the end of the SmartWire-DT ribbon cable Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position As required Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Damp heat, cons...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-RC8-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.