

INDUSTRIAL COMPONENT DATA

NZM3-XAD630 107206 Y7-107206 EATON ELECTRIC Busbar adapter, 3p, for NZM3, 630A, UL508

Brand: EATON - MOELLER | Manufacturer Part Number: NZM3-XAD630



Manufacturer	EATON - MOELLER
MPN / Reference	NZM3-XAD630
Catalog number	Y7-107206
Category	Busbar adapter
Minimum order	1 Pcs
Document ID	EO-0342887AE8
Generated	2026-08-06

Product Overview

Busbar adapter, 3p, for NZM3, 630A, UL508

NZM3-XAD630

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Busbar adapter, 3p, for NZM3, 630A, UL508

Type-checked busbar adapter for NZM circuit-breaker and N switch-disconnector, for surface mounting on Cu-busbars 12-30x5-10, double t and triple t profile, rated operational current $I_e=630A$, can be used for NZM3, PN3, N3, adapter width=140mm, rated operating voltage $U_e=690VAC$, screw connection on the busbar 5mm or 10mm thickness, connection top or bottom possible by turning the adapter, temperature resistant to 120 °C, self-extinguishing to UL 94, track resistance CTI 200, number of poles=3 pole, between busbar centers=60mm, can be used in conjunction with busbar system SASY 60i, UL approved, observe derating

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton xEffect SASY 60i MCCB adapter Catalog Number 107206 Model Code NZM3-XAD630 EAN

4015081069699 Product Length/Depth 272 mm Product Height 35 mm Product Width 140 mm Product Weight 2.342 kg

Compliances UL CSA09 (refer to approbation report)

IEC 60439-1

UL508A

CE marking

CSA-C22.2 No. 14

RoHS conform Certifications North America (UL listed, CSA certified)

CSA (File No. 236217)

UL (File No. E300273)

UL (Category Control Number NMTR, NMTR7)

CSA (Class No. 3211-37) Catalog Notes For surface mounting on flat copper busbars 12 - 30 x 5 - 10, double T and triple T profile Delivery program

Type Nominal current 630 A Number of poles Three-pole Technical data - electrical

Voltage rating (UL CSA 13) Max. 600 V AC Voltage rating at AC 690 V AC Rated operation current (Ie) 630 A Electric connection type Other Creepage resistance CTI 200 Technical data - mechanical

Mounting rail armament None Rail width 30 mm Degree of protection Feeder circuits Busbar distance 60 mm Busbar thickness - min 5 mm Busbar thickness - max 10 mm Busbar adapter width 140 mm Adapter width 140 mm Design verification as per IEC/EN 61439 - technical data

Equipment heat dissipation, current-dependent Pvid 61.8 W Temperature resistance Up to 120 °C Additional information

Features Self-extinguishing acc. UL 94 Functions Busbar adapters for NZM

Current limiting circuit breaker, refer to approbation report

Component adapter for circuit breakers and switch-disconnector Suitable for S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM3-XAD630 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.