

INDUSTRIAL COMPONENT DATA

BBA0C-16 101455 Y7-101455 EATON ELECTRIC Busbar adapter, 45mm, 16A, 2TS cage

Brand: EATON - MOELLER | Manufacturer Part Number: BBA0C-16



Manufacturer	EATON - MOELLER
MPN / Reference	BBA0C-16
Catalog number	Y7-101455
Category	Busbar adapter
Minimum order	4 Pcs
Document ID	EO-08B154DCD4
Generated	2026-08-05

Product Overview

Busbar adapter, 45mm, 16A, 2TS cage

BBA0C-16

Eaton Moeller® series BBA Busbar adapter, 45 mm, 16 A, DIN rail: 2

45mm busbar adapter for 60mm busbar system, two mounting rails, three prefabricated cables (AWG14/2.5 square millimeter) for connection of switching device with spring-loaded terminals in the feeder circuit, can be used for motor-protective circuit-breaker PKZM0-...-C or motor-starter combination with PKZM0-...-C and contactor DILM(C)7 to DILM(C)15, rated operational current: 16A, rated operational current according to UL508: 12A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

Additional Product Information

General specifications

Product Name Eaton Moeller® series BBA Accessory Busbar adapter Catalog Number 101455 Model Code BBA0C-16

EAN 4015081013753 Product Length/Depth 200 mm Product Height 63 mm Product Width 45 mm Product Weight 0.28 kg

Certifications CE

IEC60439-1

CSA-C22.2 No. 14

UL File No.: E300273

UL 508A

Certified by UL for use in Canada

UL Category Control No.: NMTR; NMTR7

UL

UL 508 Catalog Notes This item can only be ordered until December 31, 2023 with a maximum delivery date of May 31, 2024. Delivery program

Type Nominal current 16 A Technical data - electrical

Voltage rating (UL CSA 13) 600 V AC, UL/CSA Voltage rating at AC 690 V Rated operation current (Ie) 16 A Electric connection type Round conductor Technical data - mechanical

Mounting rail armament 2 mounting rails Rail width 35 mm Number of DIN rails 2 Busbar distance 60 mm Busbar thickness - min 5 mm Busbar thickness - max 10 mm Adapter width 45 mm Design verification as per IEC/EN 61439 - technical data Equipment heat dissipation, current-dependent Pvid 0.8 W Static heat dissipation, non-current-dependent Pvs 0 W Heat dissipation per pole, current-dependent Pvid 0 W Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA0C-16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.