

**INDUSTRIAL COMPONENT DATA**

# BBA0-25/2TS 101481 Y7-101481 EATON ELECTRIC Busbar adapter, 45mm, 25A, 2TS

Brand: EATON - MOELLER | Manufacturer Part Number: BBA0-25/2TS



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | BBA0-25/2TS     |
| Catalog number  | Y7-101481       |
| Category        | Busbar adapter  |
| Minimum order   | 4 Pcs           |
| Document ID     | EO-ECB2212CF1   |
| Generated       | 2026-08-04      |

## Product Overview

Busbar adapter, 45mm, 25A, 2TS

BBA0-25/2TS

Eaton Moeller® series BBA Busbar adapter, 45 mm, 25 A, DIN rail: 2

45mm busbar adapter for 60mm busbar system, two mounting rails, three prefabricated cables (AWG12/4 square millimeter) for connection of switching device, can be used universally, mounting rails can be moved within a 1.25 mm grid, rated operational current: 25A

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

## Additional Product Information

General specifications

Product Name Eaton Moeller® series BBA Accessory Busbar adapter Catalog Number 101481 Model Code BBA0-25/2TS  
EAN 4015081014019 Product Length/Depth 200 mm Product Height 73 mm Product Width 45 mm Product Weight 0.282 kg  
Certifications UL 508A

UL

Certified by UL for use in Canada

CSA-C22.2 No. 14

IEC60439-1

UL Category Control No.: NMTR; NMTR7

UL 508

UL File No.: E300273

CE Delivery program

Type Nominal current 25 A Technical data - electrical

Voltage rating (UL CSA 13) 600 V AC, UL/CSA Voltage rating at AC 690 V Rated operation current (Ie) 25 A Electric connection type 3 conductors AWG 12 Technical data - mechanical

Mounting rail armament 2 mounting rails Rail width 35 mm Number of DIN rails 2 Busbar distance 60 mm Busbar thickness - min 5 mm Busbar thickness - max 10 mm Adapter width 45 mm Design verification as per IEC/EN 61439 - technical data Equipment heat dissipation, current-dependent P<sub>vid</sub> 1.9 W Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W Heat dissipation per pole, current-dependent P<sub>vid</sub> 0 W Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to a...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA0-25/2TS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.