


INDUSTRIAL COMPONENT DATA

NZM2-4-XAD250 138388 Y7-138388 EATON ELECTRIC Busbar adapter, 4p, for NZM2, 250A, UL508

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2-4-XAD250



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2-4-XAD250
Catalog number	Y7-138388
Category	Busbar adapter
Minimum order	1 Pcs
Document ID	EO-B16188FA7F
Generated	2026-08-04

Product Overview

Busbar adapter, 4p, for NZM2, 250A, UL508

NZM2-4-XAD250

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Busbar adapter, 4p, for NZM2, 250A, UL508

Type-checked busbar adapter for NZM circuit-breaker and N switch-disconnector, for surface mounting on Cu-busbars 12-30x5-10, double t and triple t profile, rated operational current $I_e=250A$, can be used for NZM2, PN2, N(S)2, NZM2(-4), PN2(-4), N(N/O)2(-4), adapter width=140mm, rated operating voltage $U_e=690VAC$, screw connection on the busbar 5mm or 10mm thickness, cable connection at bottom, temperature resistant to 120 °C, self-extinguishing to UL 94, track resistance CTI 200, number of poles=4 pole, between busbar centers=60mm, can be used in conjunction with busbar system SASY 60i

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

General specifications

Product Name Eaton xEffect SASY 60i MCCB adapter Catalog Number 138388 Model Code NZM2-4-XAD250 EAN 4015081351688 Product Length/Depth 35 mm Product Height 270 mm Product Width 140 mm Product Weight 1.8 kg

Compliances RoHS conform Delivery program

Type Nominal current 250 A Number of poles Four-pole Technical data - electrical

Voltage rating at AC 690 V AC Rated operation current (I_e) 250 A Electric connection type Other Creepage resistance CTI 200 Technical data - mechanical

Mounting rail armament None Rail width 30 mm Busbar distance 60 mm Busbar thickness - min 5 mm Busbar thickness - max 10 mm Busbar adapter width 140 mm Adapter width 140 mm Design verification as per IEC/EN 61439 - technical data Equipment heat dissipation, current-dependent Pvid 8.1 W Temperature resistance Up to 120 °C Additional information Features Self-extinguishing acc. UL 94 Functions Busbar adapters for NZM Component adapter for circuit breakers and switch-disconnector Suitable for Surface mounting on flat copper busbars 12 - 30 x 5 - 10, double T and triple T profile Used with NZM2(-4), PN2(-4), N2(-4) ETIM for 138388 Low-voltage industrial controls and switchgear (EC001531)

Feature Name	Feature Value
Mounting rail armament (EF003700)	None
Type of electric connection (EF003961)	Other
Rated current In (EF008250)	250 A
Min. busbar thickness (EF006536)	5 mm
Max. busbar thickness (EF003702)	10 mm
Width of the adapter (EF003703)	140 mm
Rail width (EF003704)	30 mm
Busbar distan...	

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2-4-XAD250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.