

INDUSTRIAL COMPONENT DATA

BBA4/2TS-L 101483 Y7-101483 EATON ELECTRIC Busbar adapter, 54mm, 2TS empty module

Brand: EATON - MOELLER | Manufacturer Part Number: BBA4/2TS-L



Manufacturer	EATON - MOELLER
MPN / Reference	BBA4/2TS-L
Catalog number	Y7-101483
Category	Busbar adapter
Minimum order	4 Pcs
Document ID	EO-A1F0840909
Generated	2026-08-01

Product Overview

Busbar adapter, 54mm, 2TS empty module

BBA4/2TS-L

Eaton Moeller® series BBA Busbar adapter, 55 mm, DIN rail: 2

45mm busbar adapter for 60mm busbar system, two mounting rails, without electrical contact, for surface mounting of reversing starters and star-delta starters, mounting rails can be moved within a 1.25 mm grid

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series BBA Accessory Busbar adapter Catalog Number 101483 Model Code BBA4/2TS-L

EAN 4015081014033 Product Length/Depth 260 mm Product Height 63 mm Product Width 55 mm Product Weight 0.262 kg

Certifications CE

Certified by UL for use in Canada

IEC60439-1

UL

UL 508

UL File No.: E300273

CSA-C22.2 No. 14

UL 508A

UL Category Control No.: NMTR; NMTR7 Delivery program

Type Nominal current 0 A Technical data - electrical

Voltage rating (UL CSA 13) 600 V AC, UL/CSA Electric connection type None Technical data - mechanical

Mounting rail armament 2 mounting rails Rail width 35 mm Number of DIN rails 2 Busbar distance 60 mm Busbar thickness

- min 5 mm Busbar thickness - max 10 mm Adapter width 54 mm Design verification as per IEC/EN 61439 - technical data

Equipment heat dissipation, current-dependent Pvid 0 W Static heat dissipation, non-current-dependent Pvs 0 W Heat

dissipation per pole, current-dependent Pvid 0 W Ambient operating temperature - min -25 °C Ambient operating

temperature - max 55 °C Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of

enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal

heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect.

effects Meets the product standard's requir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA4/2TS-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.