

INDUSTRIAL COMPONENT DATA

BBA4L-63 101459 Y7-101459 EATON ELECTRIC Busbar adapter, 55mm, 63A, 2TS

Brand: EATON - MOELLER | Manufacturer Part Number: BBA4L-63



Manufacturer	EATON - MOELLER
MPN / Reference	BBA4L-63
Catalog number	Y7-101459
Category	Busbar adapter
Minimum order	4 Pcs
Document ID	EO-18515959C3
Generated	2026-08-05

Product Overview

Busbar adapter, 55mm, 63A, 2TS

BBA4L-63

Eaton Moeller® series BBA Busbar adapter, 55 mm, 63 A, DIN rail: 2

55mm busbar adapter for 60mm busbar system, two mounting rails, three prefabricated cables (AWG8/10 square millimeter) for connection of switching device, can be used for DOL starter with PKZM4 / PKE65 with contactor DILM40 to DILM65, rated operational current: 63A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series BBA Accessory Busbar adapter Catalog Number 101459 Model Code BBA4L-63 EAN 4015081013791 Product Length/Depth 260 mm Product Height 63 mm Product Width 55 mm Product Weight 0.393 kg

Certifications Certified by UL for use in Canada

IEC60439-1

UL

UL 508A

CE

CSA-C22.2 No. 14

UL Category Control No.: NMTR; NMTR7

UL File No.: E300273

UL 508 Delivery program

Type Nominal current 63 A Technical data - electrical

Voltage rating (UL CSA 13) 600 V AC, UL/CSA Voltage rating at AC 690 V Rated operation current (Ie) 63 A Electric connection type Round conductor Technical data - mechanical

Mounting rail armament 2 mounting rails Rail width 35 mm Number of DIN rails 2 Busbar distance 60 mm Busbar thickness - min 5 mm Busbar thickness - max 10 mm Adapter width 55 mm Design verification as per IEC/EN 61439 - technical data Equipment heat dissipation, current-dependent P_{vid} 6.9 W Static heat dissipation, non-current-dependent P_{vs} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA4L-63 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.