

**INDUSTRIAL COMPONENT DATA**

# BBA2L-63 101480 Y7-101480 EATON ELECTRIC Busbar adapter, 72mm, 63A, 2TS

Brand: EATON - MOELLER | Manufacturer Part Number: BBA2L-63



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | BBA2L-63        |
| Catalog number  | Y7-101480       |
| Category        | Busbar adapter  |
| Minimum order   | 2 Pcs           |
| Document ID     | EO-0020ED3211   |
| Generated       | 2026-08-04      |

## Product Overview

Busbar adapter, 72mm, 63A, 2TS

BBA2L-63

Eaton Moeller® series BBA Busbar adapter, 72 mm, 63 A, DIN rail: 2

72mm busbar adapter for 60mm busbar system, two mounting rails, three prefabricated cables (AWG8/10 square millimeter) for connection of switching device, can be used for DOL starter with PKZ2 and contactor DILM7 up to DILM40, rated operational current: 63A

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

## Additional Product Information

General specifications

Product Name Eaton Moeller® series BBA Accessory Busbar adapter Catalog Number 101480 Model Code BBA2L-63 EAN 4015081014002 Product Length/Depth 260 mm Product Height 63 mm Product Width 72 mm Product Weight 0.423 kg

Certifications CE

UL

UL 508A

UL Category Control No.: NMTR; NMTR7

IEC60439-1

UL File No.: E300273

CSA-C22.2 No. 14

Certified by UL for use in Canada

UL 508 Delivery program

Type Nominal current 63 A Technical data - electrical

Voltage rating (UL CSA 13) 600 V AC, UL/CSA Voltage rating at AC 690 V Rated operation current (Ie) 63 A Electric connection type Round conductor Technical data - mechanical

Mounting rail armament 2 mounting rails Rail width 35 mm Number of DIN rails 2 Busbar distance 60 mm Busbar thickness - min 5 mm Busbar thickness - max 10 mm Adapter width 72 mm Design verification as per IEC/EN 61439 - technical data Equipment heat dissipation, current-dependent P<sub>vid</sub> 6.9 W Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W Heat dissipation per pole, current-dependent P<sub>vid</sub> 0 W Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA2L-63 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.