

INDUSTRIAL COMPONENT DATA

Z-GV-U/4 274080 EATON ELECTRIC Phase busbar, 1ph, 16qmm, fork connector, 4SU

Brand: EATON - MOELLER | Manufacturer Part Number: Z-GV-U/4



Manufacturer	EATON - MOELLER
MPN / Reference	Z-GV-U/4
Catalog number	274080
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-739A4217C0
Generated	2026-08-05

Product Overview

Phase busbar, 1ph, 16qmm, fork connector, 4SU

Connection comb, 1ph, 16 mm², fork, 4SU

Z-GV-U/ busbars are designed to enable you to implement all popular arrester combinations, for use with SPI-...SPB-D-125, the busbars must be cut to length as necessary

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Phase busbar, 1ph, 16qmm, fork connector, 4SUZ-GV-U/ busbars are designed to enable you to implement all popular arrester combinations, for use with SPI-...SPB-D-125, the busbars must be cut to length as necessaryTechnical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar ( [ACN992011])Number of phases1Number of poles4Suitable for number of devices4Pitch dimensions17.8 mmCross section16 mm²Length70.6 mmNumber of modular spacings4Rated permanent current Iu63 AType of electric connectionForkInsulatedYesRated surge voltage0 kVConditioned rated short-circuit current Iq0 kAMax. rated operation voltage Ue400 VRated short-time withstand current Icw0 kASuitable for devices with N-busbarYesSuitable for devices with auxiliary switchNo

ETIM for 274080 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

1

Number of poles (EF001391)

4

Module width (EF007504)

17.8 mm

Cross section (EF000649)

16 mm²

Length (EF001438)

18.7 mm

Can be cut to size (EF015250)

No

Width in number of modular spacings (EF002950)

4

Rated permanent current I_u (EF001389)

63 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

0 kV

Conditioned rated short-circuit current I_q (EF001444)

0 kA

Max. rated opera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-GV-U/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.