

INDUSTRIAL COMPONENT DATA

Z-GV-16/3P-3TE 271064 0001657117 EATON ELECTRIC

Busbar, isolated, 80A, 3p, 3Mod

Brand: EATON - MOELLER | Manufacturer Part Number: Z-GV-16/3P-3TE



Manufacturer	EATON - MOELLER
MPN / Reference	Z-GV-16/3P-3TE
Catalog number	0001657117
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-49E7292951
Generated	2026-08-06

Product Overview

Busbar, isolated, 80A, 3p, 3Mod

Connection comb, 80A, 3p, 3Mod

Block busbar for PLS.CLS.PKN.PFIM, PFHM, Z-SLS/D01 (also with auxiliary contact), cover caps are not included as standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

EL-Nummer (Norway)0001657117Busbar, isolated, 80A, 3p, 3ModBlock busbar for PLS.CLS.PKN.PFIM, PFHM, Z-SLS/D01 (also with auxiliary contact), cover caps are not included as standardTechnical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar ( [ACN992011])Number of phases3Number of poles3Suitable for number of devices19Pitch dimensions0 mmCross section16 mm²Length1000 mmNumber of modular spacings3Rated permanent current Iu80 AType of electric connectionForkInsulatedYesRated surge voltage0 kVConditioned rated short-circuit current Iq0 kAMax. rated operation voltage Ue415 VRated short-time withstand current Icw0 kASuitable for devices with N-busbarNoSuitable for devices with auxiliary switchNo

ETIM for 271064 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

3

Number of poles (EF001391)

3

Suitable for number of devices (EF007241)

19

Module width (EF007504)

0 mm

Cross section (EF000649)

16 mm²

Length (EF001438)

30 mm

Can be cut to size (EF015250)

Yes

Width in number of modular spacings (EF002950)

3

Rated permanent current I_u (EF001389)

80 A

Type of electric connection (EF003961)

Fork

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

4.5 kV

Conditioned rated short-circuit current I_q (EF001444)

0 kA

Max. rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-GV-16/3P-3TE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.