

INDUSTRIAL COMPONENT DATA

RS333-50FORMP 093559 EATON ELECTRIC Busbar mounting fuse, 63A, 690 V, DIII/E33, gauge ring

Brand: EATON - MOELLER | Manufacturer Part Number: RS333-50FORMP



Manufacturer	EATON - MOELLER
MPN / Reference	RS333-50FORMP
Catalog number	093559
Category	D-system fuse base
Minimum order	1 Pcs
Document ID	EO-512CD71696
Generated	2026-08-05

Product Overview

Busbar mounting fuse, 63A, 690 V, DIII/E33, gauge ring

Fuse base, rated operational current 63A, rated operating voltage 690V, frame size DIII/E33, gauge ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Industrial Fuse Bases
--------------	---

Additional Product Information

Busbar mounting fuse, 63A, 690 V, DIII/E33, gauge ring Fuse base, rated operational current 63A, rated operating voltage 690V, frame size DIII/E33, gauge ring [Delivery program

Gauge screw system Rated operational current [Ie] 63 A Rated operational voltage [Ue] 380, 690 V Max. fuse E33, DIII A

For use with CU20X5

CU20X10

CU20X15 Notes Gauge rings/gauge screws, fuse cartridges and fuse caps not included as standard.

, Technical data

General Standards Load carrying capacity of fuse enclosures taking into account the derating factors to IEC/EN 60439 and VDE 0660 Part 500 and Part 504, and the cross-sections of the incoming cable. StandardsFuse bases: S27(-1), S33(-1)

VDE 0636

CEE 16 StandardsProtective covers VDE 0636 StandardsGauge ring system DIN 49326

DIN 49327

DIN 49524 StandardsRS27 (33)-3/FORMP gauge screw system DIN 49510 Ambient temperature -5 - +25 (+40, where annual and 24-hour mean value ? 35) °C Mounting position As required Rated uninterrupted current [Iu] 63 A Contacts

Rated operational voltage [Ue] 690 V AC Creepage and clearance distances VDE 0636 Part 31 Current heat loss per contact at rated uninterrupted current I_u 7.5 W Terminal capacitiesSolid 2.5 - 16 mm² Terminal capacitiesFlexible with ferrule 1.5 - 25 mm² , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse base (EC000094) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Diazed fuse base ()

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RS333-50FORMP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.