

INDUSTRIAL COMPONENT DATA

K30X10PEN 084350 Y7-84350 EATON ELECTRIC Busbar terminal, 1600A, for copper band

Brand: EATON - MOELLER | Manufacturer Part Number: K30X10PEN



Manufacturer	EATON - MOELLER
MPN / Reference	K30X10PEN
Catalog number	Y7-84350
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-1B0A0FC70A
Generated	2026-08-05

Product Overview

Busbar terminal, 1600A, for copper band

Terminal mud, 1600A, for PEN copper connection

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar terminal, 1600A, for copper band, PEN

Busbar terminals, for CI busbar enclosures, connection of flat cable and Cu bar on main busbar CI, can be used for busbars 1x (30x10), terminal capacity for flat cable=1x50x12, for PEN conductor, PE, N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci busbar enclosure accessory Catalog Number 084350 Model Code K30X10PEN
EAN 4015080843504 Product Length/Depth 40 mm Product Height 30 mm Product Width 40 mm Product Weight 0.301 kg
Compliances RoHS conform Product specifications

Special features For protective or neutral conductor PE, N, PEN Type Accessory/spare part type Busbar terminals Used
with Cu 1 x (30 mm x 10 mm) busbars

Ci insulated enclosure

Prepared enclosures

Accessory for busbar enclosures Width clamp 17 mm Busbar thickness - max 10 mm Busbar thickness - min 10 mm Busbar
width - max 60 mm Busbar width - min 30 mm Conductor cross section - max 1000 mm² Rated operational current (Ie) -
max 1600 A Functions Connection for flat cable and cu bar Suitable for Flat rail

Strip conductor connection Rated operational current 1600 A Terminal capacity (flat strip) 50 mm x 12 mm

ETIM for 084350 Low-voltage industrial controls and switchgear (EC000001)

Feature Name

Feature Value

Busbar thickness (EF007220)

10 mm

Busbar width (EF007219)

30 mm

Suitable for (EF000073)

Flat rail

Width clamp (EF007092)

17 mm

Max. conductor cross section (EF004969)

1000 mm²

Max. rated operation current I_e (EF007356)

1600 A

Suitable for round conductor connection (EF007258)

No

Suitable for sector conductor connection (EF007260)

No

Suitable for strip conductor connection (EF007242)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K30X10PEN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.