

INDUSTRIAL COMPONENT DATA

K20X15/40-A 012783 Y7-12783 EATON ELECTRIC Busbar terminal f. CU20x5(x10, x15)

Brand: EATON - MOELLER | Manufacturer Part Number: K20X15/40-A



Manufacturer	EATON - MOELLER
MPN / Reference	K20X15/40-A
Catalog number	Y7-12783
Category	Busbar terminal
Minimum order	10 Pcs
Document ID	EO-AE04BEE6A8
Generated	2026-08-05

Product Overview

Busbar terminal f. CU20x5(x10, x15)

bar distributor for CU20x5(x10, x15)

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar terminal f. CU20x5(x10, x15)

Ultra-flat busbar terminal, for CI fuse enclosures and SE-RS-I43 busbar assemblies, terminal capacity for flat cable=3x9x0.8 or 10x16x0.8, for Cu 20x5 / 20x10 / 20x15 busbars

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci busbar enclosure accessory Catalog Number 012783 Model Code K20X15/40-A
EAN 4015080127833 Product Length/Depth 42 mm Product Height 50 mm Product Width 42 mm Product Weight 0.075 kg

Compliances RoHS conform Product specifications

Special features Type Ci insulated enclosure

Modular busbar system

Prepared enclosures

Accessory/spare part type Terminal Used with Cu 20 x 10 mm

Cu 20 x 15 mm

Cu 20 x 5 mm

Ci insulated enclosure

Modular busbar system

Prepared enclosures Width clamp 32 mm Unit type Modular system Busbar thickness - max 10 mm Busbar thickness - min 5 mm Busbar width - max 20 mm Busbar width - min 20 mm Conductor cross section - max 124 mm² Rated operational current (Ie) - max 400 A Functions For fuse enclosures and busbar fuse enclosures as well as SE-RS-I43 busbar assemblies Suitable for Round conductor connection

Strip conductor connection

Flat rail Rated operational current 400 A

ETIM for 012783 Low-voltage industrial controls and switchgear (EC000001)

Feature Name

Feature Value

Busbar thickness (EF007220)

5 mm

Busbar width (EF007219)

20 mm

Suitable for (EF000073)

Flat rail

Width clamp (EF007092)

32 mm

Max. conductor cross section (EF004969)

124 mm²

Max. rated operation current Ie (EF007356)

400 A

Suitable for round conductor connection (EF007258)

Yes

Suitable for sector conductor connection (EF007260)

No

Suitable for strip conductor connection (EF007242)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K20X15/40-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.