

INDUSTRIAL COMPONENT DATA

K20X5 002286 Y7-2286 EATON ELECTRIC Busbar terminal, for CU 20x5

Brand: EATON - MOELLER | Manufacturer Part Number: K20X5



Manufacturer	EATON - MOELLER
MPN / Reference	K20X5
Catalog number	Y7-2286
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-4FD6426D4F
Generated	2026-08-05

Product Overview

Busbar terminal, for CU 20x5

bar distributor for CU 20x5

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar terminal, for CU 20x5

Busbar terminals, for CI busbar enclosures, for connection of flat or round conductor, can be used for busbars Cu 20x5, terminal capacity for flat cable=3x9x0.8 up to 6x16x0.8, terminal capacity for round cable=35-70, 35-50mm², rated operational current Ie=100A-250A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci busbar enclosure accessory Catalog Number 002286 Model Code K20X5 EAN 4015080022862 Product Length/Depth 20 mm Product Height 20 mm Product Width 20 mm Product Weight 0.175 kg

Compliances RoHS conform Product specifications

Used with Cu 20 x 5 mm busbars

Accessory for busbar enclosures

Ci insulated enclosure

Prepared enclosures Type Accessory/spare part type Busbar terminals Width clamp 38 mm Busbar thickness - max 5 mm

Busbar thickness - min 5 mm Busbar width - max 20 mm Busbar width - min 20 mm Conductor cross section - max 70 mm²

Rated operational current (Ie) - max 250 A Functions For connection of flat strip or round conductor Rated operation current

(Ie) 200 A
160 A
250 A
100 A Suitable for Round conductor connection
Strip conductor connection
Sector conductor connection
Flat rail Rated operational current 250 A Terminal capacity (flat strip) 16 mm x 0.8 mm (4x)
9 mm x 0.8 mm (6x)
9 mm x 0.8 mm (3x)
16 mm x 0.8 mm (6x) Terminal capacity (round conductor) 35 mm² - 70 mm²
35 mm² - 50 mm²
ETIM for 002286 Low-voltage industrial controls and switchgear (EC000001)
Feature Name
Feature Value
Busbar thickness (EF007220)
5 mm
Busbar width (EF007219)
20 mm
Suitable for (EF000073)
Flat rail
Width clamp (EF007092)
38 mm
Max. conductor cross section (EF004969)
70 mm²
Max. rated operation current Ie (EF007356)
250 A
Suitable for round conductor connection (EF007258)
Yes
Suitable for sector conductor connection (EF007260)
Ye...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K20X5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.