

INDUSTRIAL COMPONENT DATA

K20X15/40 002285 Y7-2285 EATON ELECTRIC Busbar terminal, for CU20x5(x10, x15)

Brand: EATON - MOELLER | Manufacturer Part Number: K20X15/40



Manufacturer	EATON - MOELLER
MPN / Reference	K20X15/40
Catalog number	Y7-2285
Category	Busbar terminal
Minimum order	10 Pcs
Document ID	EO-F6A9C71D84
Generated	2026-08-05

Product Overview

Busbar terminal, for CU20x5(x10, x15)

bar distributor for CU20x5(x10, x15)

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar terminal, for CU20x5(x10, x15), busbar terminal for CU 20X15/40

Ultra-flat busbar terminal, terminal capacity for round cable=re 1.5-10 or rf 1.5-6mm², terminal capacity for flat cable=3x9x0.8 or 6x9x0.8 or 4x16x0.8 or 6x16x0.8 or 10x16x0.8 or 11x21x1, for Cu 20x10 / 20x15 busbars, rated operational current Ie=630A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci busbar enclosure accessory Catalog Number 002285 Model Code K20X15/40 EAN 4015080022855 Product Length/Depth 50 mm Product Height 40 mm Product Width 40 mm Product Weight 0.072 kg

Compliances RoHS conform Product specifications

Type Accessory/spare part type Ultra-flat busbar terminals

Busbar terminals Used with Cu 20 x 5 mm busbars

Cu 20 x 10 mm busbars

Cu 20 x 15 mm busbars

Ci insulated enclosure

Accessory for busbar enclosures

Prepared enclosures

Accessory panel building Width clamp 32 mm Busbar thickness - max 10 mm Busbar thickness - min 5 mm Busbar width - max 20 mm Busbar width - min 20 mm Conductor cross section - max 124 mm² Rated operational current (Ie) - max 400 A

Functions Terminal for flat strip Rated operation current (Ie) 100 A

400 A

200 A

160 A

630 A

250 A Suitable for Strip conductor connection

Round conductor connection

Flat rail Rated operational current 400 A Terminal capacity (flat strip) 16 mm x 0.8 mm (10x)

9 mm x 0.8 mm (6x)

16 mm x 0.8 mm (6x)

16 mm x 0.8 mm (4x)

9 mm x 0.8 mm (3x)

21 mm x 1 mm (11x) Terminal capacity (round conductor) 1.5 mm² - 10 mm²

1.5 mm² - 6 mm²

ETIM for 002285 Low-voltage industrial controls and switchgear (EC000001)

Feature Name

Feature Value

Busbar thickness (EF007220)

5 mm

Busbar width (EF007219)

20 mm

Suitable for (EF000073)

Flat rail

Width clamp (EF007092)

32 mm

Max. conductor cross section (EF004969)

124 mm²

Max. rated operation current Ie (EF007356)

400 A

Suit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K20X15/40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.