

INDUSTRIAL COMPONENT DATA

K20X15/50 002326 Y7-2326 EATON ELECTRIC Busbar terminal, for CU20x5(x10, x15)

Brand: EATON - MOELLER | Manufacturer Part Number: K20X15/50



Manufacturer	EATON - MOELLER
MPN / Reference	K20X15/50
Catalog number	Y7-2326
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-5853822DFD
Generated	2026-08-06

Product Overview

Busbar terminal, for CU20x5(x10, x15)

bar distributor for CU 20x5

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar terminal, for CU20x5(x10, x15), busbar terminal for CU 20X15/50

Ultra-flat busbar terminal, terminal capacity for round cable=re 1.5-10 or rf 1.5-6mm², terminal capacity for flat cable=11x21x1 or 2x (11x21x1), for Cu 20x15 busbars, rated operational current Ie=800A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci busbar enclosure accessory Catalog Number 002326 Model Code K20X15/50 EAN 4015080023265 Product Length/Depth 60 mm Product Height 40 mm Product Width 40 mm Product Weight 0.086 kg

Compliances RoHS conform Product specifications

Type Accessory/spare part type Busbar terminals

Ultra-flat busbar terminals Used with Cu 20 x 15 mm busbars

Ci insulated enclosure

Prepared enclosures

Accessory for busbar enclosures

Accessory panel building Width clamp 31 mm Busbar thickness - max 15 mm Busbar thickness - min 5 mm Busbar width -

max 20 mm Busbar width - min 20 mm Conductor cross section - max 462 mm² Rated operational current (I_e) - max 800 A

Functions Terminal for flat strip Rated operation current (I_e) 630 A

800 A Suitable for Strip conductor connection

Flat rail

Round conductor connection Rated operational current 800 A Terminal capacity (flat strip) 2 segments of 21 mm x 1 mm (11x)

21 mm x 1 mm (11x) Terminal capacity (round conductor) 1.5 mm² - 10 mm²

1.5 mm² - 6 mm²

ETIM for 002326 Low-voltage industrial controls and switchgear (EC000001)

Feature Name

Feature Value

Busbar thickness (EF007220)

5 mm

Busbar width (EF007219)

20 mm

Suitable for (EF000073)

Flat rail

Width clamp (EF007092)

31 mm

Max. conductor cross section (EF004969)

462 mm²

Max. rated operation current I_e (EF007356)

800 A

Suitable for round conductor connection (EF007258)

Yes

Suitable for sector conductor connection (EF007260)

No

Suitable for strip conducto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / K20X15/50 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.