

INDUSTRIAL COMPONENT DATA

Z-SV-10/1P+N-SD 269526 Y7-269526 EATON ELECTRIC Busbars 2Ph., for Z-SD230 Schuko socket, 50A

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV-10/1P+N-SD



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV-10/1P+N-SD
Catalog number	Y7-269526
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-2BAED137C2
Generated	2026-08-04

Product Overview

Busbars 2Ph., for Z-SD230 Schuko socket, 50A

Z-SV-10/1P+N-SD

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 269526 Model Code Z-SV-10/1P+N-SD EAN 4015082695262

Product Length/Depth 29 mm Product Height 15 mm Product Width 1020 mm Product Weight 0.322 kg Compliances RoHS conform Product specifications

Features Insulated

Can be cut to size Electric connection type Pin Rated surge voltage 4 kV Rated uninterrupted current (Iu) 50 A Suitable for number of devices 13 Number of poles Single-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm² Number of modular spacings 1 Number of phases 2 Pitch dimensions 0 mm Rated operational voltage (Ue) - max 415 V Rated conditional short-circuit current (Iq) 0 kA

ETIM for 269526 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

2

Number of poles (EF001391)

1

Suitable for number of devices (EF007241)

13

Module width (EF007504)

0 mm

Cross section (EF000649)

10 mm²

Length (EF001438)

29 mm

Can be cut to size (EF015250)

Yes

Width in number of modular spacings (EF002950)

1

Rated permanent current I_u (EF001389)

50 A

Type of electric connection (EF003961)

Pin

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

4 kV

Conditioned rated short-circuit current I_q (EF001444)

0 kA

Max. rated operation voltage U_e (EF007357)

415 V

Rated short-time withstand current I_{cw} (EF007050)

0 kA

Suitable for devices with N-conductor (EF007218)

No

Suitable for devices with auxiliary switch (EF007217)

No

Col...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV-10/1P+N-SD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.