

INDUSTRIAL COMPONENT DATA

BUSS MIDGET FUSE FNM-12 EATON ELECTRIC Fused disconnecter, low voltage, 30 A, AC 240 V, UL midget, IEC 10 X ..

Brand: EATON - MOELLER | Manufacturer Part Number: BUSS MIDGET FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	BUSS MIDGET FUSE
Catalog number	FNM-12
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-102524745C
Generated	2026-08-06

Product Overview

Fused disconnecter, low voltage, 30 A, AC 240 V, UL midget, IEC 10 x 38, AC23A, 1P, UL, IEC

BUSS MIDGET FUSE

BUSS MIDGET FUSE - Fuse-link, low voltage, 12 A, AC 250 V, 10 x 38 mm, supplemental, UL, CSA, colour-coded, green, time-delay

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, low voltage, 12 A, AC 250 V, 10 x 38 mm, supplemental, UL, CSA, colour-coded, green, time-delayFuse,

Fuse-link, low voltage, 12 A, AC 250 V, 10 x 38 mm, supplemental, UL, CSA, time-delay, cylindrical, colour-coded, green, general purpose, lighting circuits, meter circuits, UL 248-14, melamine tubeDelivery program

Product rangeFuseBasic functionFuse-linkField of applicationlow voltageRated current [I]12 ARated voltageAC 250

VSize10 x 38 mmUtilization categorysupplementalDescriptioncolour-coded

greenusable for size/applicationsgeneral purpose, lighting circuits, meter circuitsRelease characteristic

[class]time-delayStandard/ApprovalUL

CSAShapecylindricalMaterialmelamine tubeStandards/RegulationsUL 248-14Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ()

[AFZ797013])Size10x38 mmRated voltage250 - 250 VRated voltageOtherVoltage typeACUtilization categoryOtherRated operating frequency45 - 62 HzNominal current12 AWith strikerNoRelease characteristicM (Midget)Breaking capacity10 kA

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BUSS MIDGET FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.