

## INDUSTRIAL COMPONENT DATA

# BUSS MIDGET FUSE FNQ-12 EATON ELECTRIC Fused disconnecter, low voltage, 30 A, AC 240 V, UL midget, IEC 10 X ..

Brand: EATON - MOELLER | Manufacturer Part Number: BUSS MIDGET FUSE



|                 |                  |
|-----------------|------------------|
| Manufacturer    | EATON - MOELLER  |
| MPN / Reference | BUSS MIDGET FUSE |
| Catalog number  | FNQ-12           |
| Category        | Cylindrical fuse |
| Minimum order   | 10 Pcs           |
| Document ID     | EO-E6FCCBF115    |
| Generated       | 2026-08-06       |

## Product Overview

Fused disconnecter, low voltage, 30 A, AC 240 V, UL midget, IEC 10 x 38, AC23A, 1P, UL, IEC

BUSS MIDGET FUSE

BUSS MIDGET FUSE - Fuse-link, low voltage, 12 A, AC 500 V, 200 kA, 10 x 38 mm, 13/32 x 1-1/2 inch, supplemental, UL, colour-coded, time-delay

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

## Additional Product Information

Fuse-link, low voltage, 12 A, AC 500 V, 200 kA, 10 x 38 mm, 13/32 x 1-1/2 inch, supplemental, UL, colour-coded, time-delay  
Fuse, fuse-link, low voltage, 12 A, AC 500 V, 10 x 38 mm, 13/32 x 1-1/2 inch, Class supplemental, UL, time-delay, cylindrical, colour-coded, for motor control transformers and circuits with in-rush currents, Fiber tube construction, Nickel-plated brass endcaps  
Delivery program

Product range Fuse  
Basic function Fuse-link  
Field of application low voltage  
Rated current [I]<sub>N</sub> 12 A  
Rated voltage AC 500 V  
Size 10 x 38 mm

13/32 x 1-1/2 inch  
Utilization category supplemental  
Description colour-coded  
Breaking Capacity 200 kA  
Usable for size/applications for motor control transformers and circuits with in-rush currents  
Release characteristic

[class] time-delay  
Standard/Approval UL  
Shape cylindrical  
Material fiber tube construction  
nickel-plated brass endcaps  
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ([email protected] [AFZ797013]) Size 10x38 mm Rated voltage 500 - 500 V Rated voltage Other Voltage type AC Utilization category Other Rated operating frequency 45 - 62 Hz Nominal current 12 A With striker No Release characteristic M (Midget) Breaking capacity 10 kA

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BUSS MIDGET FUSE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.