

INDUSTRIAL COMPONENT DATA

BUSS MIDGET FUSE FNQ-14 EATON ELECTRIC Fused disconnecter, low voltage, 30 A, AC 240 V, UL midget, IEC 10 X ..

Brand: EATON - MOELLER | Manufacturer Part Number: BUSS MIDGET FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	BUSS MIDGET FUSE
Catalog number	FNQ-14
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-3F3E154AA0
Generated	2026-08-06

Product Overview

Fused disconnecter, low voltage, 30 A, AC 240 V, UL midget, IEC 10 x 38, AC23A, 1P, UL, IEC

BUSS MIDGET FUSE

BUSS MIDGET FUSE - Fuse-link, low voltage, 14 A, AC 500 V, 200 kA, 10 x 38 mm, 13/32 x 1-1/2 inch, supplemental, UL, colour-coded, time-delay

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, low voltage, 14 A, AC 500 V, 200 kA, 10 x 38 mm, 13/32 x 1-1/2 inch, supplemental, UL, colour-coded, time-delay
Fuse, fuse-link, low voltage, 14 A, AC 500 V, 10 x 38 mm, 13/32 x 1-1/2 inch, Class supplemental, UL, time-delay, cylindrical, colour-coded, for motor control transformers and circuits with in-rush currents, Fiber tube construction, Nickel-plated brass endcaps
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application low voltage
Rated current [I]¹ 14 A
Rated voltage AC 500 V
Size 10 x 38 mm

13/32 x 1-1/2 inch
Utilization category supplemental
Description colour-coded
Breaking Capacity 200 kA
Usable for size/applications for motor control transformers and circuits with in-rush currents
Release characteristic

[class] time-delay
Standard/Approval UL
Shape cylindrical
Material fiber tube construction
nickel-plated brass endcaps
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ( [AFZ797013]) Size 10x38 mm Rated voltage 500 - 500 V Rated voltage Other Voltage type AC Utilization category Other Rated operating frequency 45 - 62 Hz Nominal current 14 A With striker No Release characteristic M (Midget) Breaking capacity 10 kA

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BUSS MIDGET FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.