

INDUSTRIAL COMPONENT DATA

**BUSSMANN 300A 500V 2 GG EOU 300NHG2B EATON
ELECTRIC Fuse-link, 10x38 mm, 2A, gG**

Brand: EATON - MOELLER | Manufacturer Part Number: BUSSMANN 300A 500V 2 GG EOU



Manufacturer	EATON - MOELLER
MPN / Reference	BUSSMANN 300A 500V 2 GG EOU
Catalog number	300NHG2B
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-A0E0D16199
Generated	2026-08-06

Product Overview

Fuse-link, 10x38 mm, 2A, gG

BUSSMANN 300A 500V 2 GG EOU

Fuse-link, LV, 300 A, AC 500 V, NH2, gL/gG, IEC, dual indicator, live gripping lugs

Fuse, fuse-link, low voltage, 300 A, AC 500 V, NH2, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage NH Fuse Catalog Number 300NHG2B Model Code BUSSMANN 300A 500V 2 GG EOU EAN 5027590475884 Product Length/Depth 150 mm Product Height 71 mm Product Width 54 mm

Product Weight 651 g Compliances CE Marked

RoHS Compliant Certifications IEC 60269-1

IEC 60269-2

DIN 43620 Electrical data

Amperage Rating 300 A Voltage rating 500 V Voltage type AC Breaking capacity 120 kA Class Class gG/gL Product specification

Fuse size NH2 Insulated metal gripping lugs (IMGL) No Accessories

Suitable for SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base
Microswitch 170H0235
Microswitch 170H0236
EBH Size 00 to 4 Horizontal fuse switch-disconnectors
ETIM for 300NHG2B Circuit breakers and fuses (EC000055)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
NH2
Voltage type (EF000187)
AC
Rated current (EF000227)
300 A
Rated voltage AC (EF007682)
500 V
Rated switching capacity AC (EF017698)
120 kA
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Type of fuse status indicator (EF004473)
Combination fuse status indicator
Insulated metal gripping lugs (IMGL) (EF012538)
No
Power loss at rated current (EF012389)
20 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BUSSMANN 300A 500V 2 GG EOU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.