

INDUSTRIAL COMPONENT DATA

**BUSSMANN 32A 400V GG 000 32NHG000BI-400 EATON
ELECTRIC Fuse-link, 14x51 mm, 32A, gG**

Brand: EATON - MOELLER | Manufacturer Part Number: BUSSMANN 32A 400V GG 000



Manufacturer	EATON - MOELLER
MPN / Reference	BUSSMANN 32A 400V GG 000
Catalog number	32NHG000BI400
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-3100590D56
Generated	2026-08-06

Product Overview

Fuse-link, 14x51 mm, 32A, gG

fuse cartridge, BT 32 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, insulated metal terminals

32NHG000BI-400 - Fuse-link, LV, 32 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs

Fuse, fuse-link, low voltage, 32 A, AC 400 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann EWS fuses
--------------	--------------------------------------

Additional Product Information

Fuse-link, LV, 32 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs Fuse, fuse-link, low voltage, 32 A, AC 400 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 32 A Rated voltage AC 400 V

Construction size NH000 Utilization category gL/gG Status indicator dual (combination) indicator system Description

insulated gripping lugs Breaking Capacity 120 kA Standard/Approval IEC Shape square body with knife blade contacts

Standards/Regulations IEC 60269-2 fuse system A

DIN 43620

VDE 0636-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015]) Construction size NH000 Rated current 32 A Rated voltage 400 V Voltage type AC Rated switching capacity
120 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator Combination fuse
status indicator Insulated metal gripping lugs (IMGL) Yes
ETIM for 32NHG000BI-400 Circuit breakers and fuses (EC000055)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
NH000
Voltage type (EF000187)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BUSSMANN 32A 400V GG 000 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.