


INDUSTRIAL COMPONENT DATA

M22-XDL-W-X8 218306 Y7-218306 EATON ELECTRIC Button lens, flat white, arrow symbol

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDL-W-X8



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XDL-W-X8
Catalog number	Y7-218306
Category	Hood/lens for circuit control devices
Minimum order	1 Pcs
Document ID	EO-3A82105737
Generated	2026-08-04

Product Overview

Button lens, flat white, arrow symbol

M22-XDL-W-X8

Button lens, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Flush, Name: Directions of movement, Selection to: Symbol, For use with: M22(S)-DL-X, M22(S)-DRL-X, M22S-DGL-X, M30C-FDL-X, M30C-FDRL-X, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Button lens, flat white, arrow symbol Button lens, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Flush, Name: Directions of movement, Selection to: Symbol, For use with: M22(S)-DL-X, M22(S)-DRL-X, M22S-DGL-X, M30C-FDL-X, M30C-FDRL-X, Connection to SmartWire-DT: no

General specifications Product name Eaton Moeller® series M22 Accessory Button lens Part no. M22-XDL-W-X8 EAN4015082183066 Product Length/Depth 24 millimetre Product height 3 millimetre Product width 24 millimetre Product weight 0.002 kilogram Certifications UL/CSA certification not required Product Tradename M22 Product Type Accessory Product Sub Type Button lens Features & Functions Design Flat Inscription Individual inscription possible: ≤ 5 characters: letter height 5 mm

Individual inscription possible: > 5 characters: letter height 3 mm Lens color White Climatic environmental conditions Ambient operating temperature - max 70 °C Design verification Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified

heat dissipation (In)0 A10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard's requirements.10.2.3.3 Resist. of insul. mat. to....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDL-W-X8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.