


INDUSTRIAL COMPONENT DATA

M22-XDL-W-X8 218306 Y7-218306 EATON ELECTRIC Button lens, flat white, arrow symbol

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDL-W-X8



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XDL-W-X8
Catalog number	Y7-218306
Category	Hood/lens for circuit control devices
Minimum order	1 Pcs
Document ID	EO-3A82105737
Generated	2026-08-05

Product Overview

Button lens, flat white, arrow symbol

M22-XDL-W-X8

Button lens, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Flush, Name: Directions of movement, Selection to: Symbol, For use with: M22(S)-DL-X, M22(S)-DRL-X, M22S-DGL-X, M30C-FDL-X, M30C-FDRL-X, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Button lens, flat white, arrow symbolButton lens, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Flush, Name: Directions of movement, Selection to: Symbol, For use with: M22(S)-DL-X, M22(S)-DRL-X, M22S-DGL-X, M30C-FDL-X, M30C-FDRL-X, Connection to SmartWire-DT: no
General specificationsProduct nameEaton Moeller® series M22 Accessory Button lensPart no.M22-XDL-W-X8EAN4015082183066Product Length/Depth24 millimetreProduct height3 millimetreProduct width24 millimetreProduct weight0.002 kilogramCertificationsUL/CSA certification not requiredProduct TradenameM22Product TypeAccessoryProduct Sub TypeButton lensFeatures & FunctionsDesignFlatInscriptionIndividual inscription possible: <= 5 characters: letter height 5 mm

Individual inscription possible: > 5 characters: letter height 3 mmLens colorWhiteClimatic environmental conditionsAmbient operating temperature - max70 °CDesign verificationEquipment heat dissipation, current-dependent Pvid0 WHeat dissipation capacity Pdisso WHeat dissipation per pole, current-dependent Pvid0 WRated operational current for specified

heat dissipation (In)0 A10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard's requirements.10.2.3.3 Resist. of insul. mat. to....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDL-W-X8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.