


INDUSTRIAL COMPONENT DATA

M22-XDL-W-X13 218311 Y7-218311 EATON ELECTRIC Button lens, flat white, symbol solve

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDL-W-X13



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XDL-W-X13
Catalog number	Y7-218311
Category	Hood/lens for circuit control devices
Minimum order	10 Pcs
Document ID	EO-875A68B80F
Generated	2026-08-05

Product Overview

Button lens, flat white, symbol solve

M22-XDL-W-X13

Eaton Moeller® series M22 Button lens, flat white, symbol solve M22-XDL-W-X13

Button lens, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Flush, Name: Unclamp, Selection to: Symbol, For use with: M22(S)-DL-X, M22(S)-DRL-X, M22S-DGL-X, M30C-FDL-X, M30C-FDRL-X, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Button lens Catalog Number 218311 Model Code M22-XDL-W-X13
EAN 4015082183110 Product Length/Depth 24 mm Product Height 3 mm Product Width 24 mm Product Weight 0.002 kg
Certifications UL/CSA certification not required Features & Functions

Design Flat Inscription Individual inscription possible: ≤ 5 characters: letter height 5 mm

Individual inscription possible: > 5 characters: letter height 3 mm Lens color White General

Product category Accessories Type Button lenses Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdiss 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Please enquire 10.2.5 Lifting Does not apply,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDL-W-X13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.