

INDUSTRIAL COMPONENT DATA

M22-XD-S-GB9 218201 Y7-218201 EATON ELECTRIC Button plate, flat black, TEST

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XD-S-GB9



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XD-S-GB9
Catalog number	Y7-218201
Category	Legend plate for control circuit devices
Minimum order	10 Pcs
Document ID	EO-0705F9B2B0
Generated	2026-08-02

Product Overview

Button plate, flat black, TEST

M22-XD-S-GB9

Button plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Flush, Inscription: TEST, Selection to: Text, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Button plate, flat black, TESTButton plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Flush, Inscription: TEST, Selection to: Text, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: no

General specificationsProduct nameEaton Moeller® series M22 Accessory Button platePart no.M22-XD-S-GB9EAN4015082182014Product Length/Depth24 millimetreProduct height3 millimetreProduct width24 millimetreProduct weight0.002 kilogramCertificationsUL/CSA certification not requiredProduct TradenameM22Product TypeAccessoryProduct Sub TypeButton plateFeatures & FunctionsColorBlackDesignFlushInscriptionIndividual inscription possible: > 5 characters: letter height 3 mm

Individual inscription possible: <= 5 characters: letter height 5 mm

TESTInscription typeTextLanguageEnglishShapeRoundGeneral informationSuitable forPush buttonClimatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating temperature - max70 °CCommunicationConnection

to SmartWire-DTNoDesign verificationEquipment heat dissipation, current-dependent Pvid0 WHeat dissipation capacity
Pdiss0 WHeat dissipation per pole, current-dependent Pvid0 WRated operational current for specified heat dissipation (In)0
AStatic heat dissipation, non-current-dependent Pvs0 W10.2.2 Corrosion resistanceMeets the product standard's
requirements.10.2.3.1 Verification of thermal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XD-S-GB9 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.