


INDUSTRIAL COMPONENT DATA

M22-XD-G-X1 218165 Y7-218165 EATON ELECTRIC Button plate, flat green, I

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XD-G-X1



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XD-G-X1
Catalog number	Y7-218165
Category	Legend plate for control circuit devices
Minimum order	10 Pcs
Document ID	EO-C9FD67B5FA
Generated	2026-08-02

Product Overview

Button plate, flat green, I

M22-XD-G-X1

Eaton Moeller® series M22 Button plate, flat green, I

Button plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Design: Flush, Name: START, Selection to: Symbol, For use with: M22(S)-D-X, M22(S)-DR-X, M22-DG-X, M30C-FD-X, M30C-FDR-X, Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Button plate Catalog Number 218165 Model Code M22-XD-G-X1
EAN 4015082181659 Product Length/Depth 24 mm Product Height 3 mm Product Width 24 mm Product Weight 0.002 kg
Compliances CE Certifications UL/CSA certification not required Features & Functions
Color Green Design Flush Inscription Individual inscription possible: > 5 characters: letter height 3 mm
Individual inscription possible: <= 5 characters: letter height 5 mm
Other Inscription type Symbol Language Other Shape Round General
Product Category Accessories Suitable for Push button Type Flat Used with M22(S)-D-X
M22-DG-X
M22(S)-DR-X Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication
Connection to SmartWire-DT No Design verification
Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,
current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,
non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1
Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance
of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal
heat/fire by internal elect. effects Meets the pr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XD-G-X1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.