

INDUSTRIAL COMPONENT DATA

M22-XDP-R-X0 218157 Y7-218157 EATON ELECTRIC Button plate, mushroom red

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XDP-R-X0



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XDP-R-X0
Catalog number	Y7-218157
Category	Legend plate for control circuit devices
Minimum order	1 Pcs
Document ID	EO-F0337FF01E
Generated	2026-08-03

Product Overview

Button plate, mushroom red

M22-XDP-R-X0

Button plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Name: STOP, Selection to: Symbol, For use with: M22(S)-D(R)P-..., Connection to SmartWire-DT: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Button plate, mushroom redButton plate for push-button, Product range: Accessories, Single unit, Description: 5 characters: letter height 5 mm, > 5 characters: letter height 3 mm, Name: STOP, Selection to: Symbol, For use with: M22(S)-D(R)P-..., Connection to SmartWire-DT: no

General specificationsProduct nameEaton Moeller® series M22 Accessory Button platePart

no.M22-XDP-R-X0EAN4015082181574Product Length/Depth24 millimetreProduct height9 millimetreProduct width24

millimetreProduct weight0.002 kilogramCertificationsUL/CSA certification not requiredProduct TradenameM22Product

TypeAccessoryProduct Sub TypeButton plateFeatures & FunctionsColorRedInscriptionIndividual inscription possible: <= 5 characters: letter height 5 mm

Individual inscription possible: > 5 characters: letter height 3 mm

OtherInscription typeSymbolLanguageOtherShapeRoundGeneral informationSuitable forMushroom head push buttonUsed withM22(S)-D(R)P-...Climatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating

temperature - max70 °C
Communication
Connection to SmartWire-DT
NoDesign verification
Equipment heat dissipation,
current-dependent P_{vid0} W
Heat dissipation capacity P_{diss0} W
Heat dissipation per pole, current-dependent P_{vid0} W
Rated operational current for specified heat dissipation (I_n)0 A
Static heat dissipation, non-current-dependent P_{vs0} W
10.2.2
Corrosion resistance
Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures
Meets the product....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XDP-R-X0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.