


## INDUSTRIAL COMPONENT DATA

# 921TQ25 047426 Y7-47426 EATON ELECTRIC Button plate, symbol liquid START

Brand: EATON - MOELLER | Manufacturer Part Number: 921TQ25



|                 |                                          |
|-----------------|------------------------------------------|
| Manufacturer    | EATON - MOELLER                          |
| MPN / Reference | 921TQ25                                  |
| Catalog number  | Y7-47426                                 |
| Category        | Legend plate for control circuit devices |
| Minimum order   | 1 Pcs                                    |
| Document ID     | EO-BDFBA58B2D                            |
| Generated       | 2026-08-05                               |

## Product Overview

Button plate, symbol liquid START

Inscription Indicator Plate: Black "Liquid" Symbol for RMQ16 25x25

Eaton Moeller® series RMQ16 Button plate for push-button, Name: Liquid START, 25 x 25

Button plate for push-button, Product range: Accessories, Single unit, Name: Liquid START, Connection to SmartWire-DT: no

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

## Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Accessory Button plate Catalog Number 047426 Model Code 921TQ25 EAN 4015080474265 Product Length/Depth 19 mm Product Height 19 mm Product Width 3 mm Product Weight 0.009 kg

Certifications UL/CSA certification not required Features & Functions

Color White Inscription Other Shape Square General

Product Category Accessories Size 25 × 25 mm Suitable for Push button Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole, current-dependent Pvid 0 W Rated operational current for specified heat dissipation (In) 0 A Static heat dissipation, non-current-dependent Pvs 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Please enquire 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical impact Does not apply, since the entire switc...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 921TQ25 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.