

INDUSTRIAL COMPONENT DATA

BXS25 25AMP FUSE LINK FOR SASIL FUSE SWITCH EATON

ELECTRIC Fuse-link, low voltage, 10 A, AC 440 V, 26 x 100 ..

Brand: EATON - MOELLER | Manufacturer Part Number: BXS25



Manufacturer	EATON - MOELLER
MPN / Reference	BXS25
Catalog number	25AMP FUSE LINK FOR SASIL FUSE SWITCH
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-F11137A721
Generated	2026-08-03

Product Overview

Fuse-link, low voltage, 10 A, AC 440 V, 26 x 100 mm, gL/gG, BS

25AMP FUSE LINK FOR SASIL FUSE SWITCH

25AMP FUSE LINK FOR SASIL FUSE SWITCH - Fuse-link, low voltage, 25 A, AC 440 V, 80 kA, 26 x 100 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 25 A, AC 440 V, 26 x 100 mm, gL/gG, BS, cylindrical, offset-bolted tags, for SASIL fuse switch, Breaking Capacity 80 kA, Optional accessories, Supplied with

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 25 A, AC 440 V, 80 kA, 26 x 100 mm, gL/gG, BS Fuse, Fuse-link, low voltage, 25 A, AC 440 V, 26 x 100 mm, gL/gG, BS, cylindrical, offset-bolted tags, for SASIL fuse switch, Breaking Capacity 80 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I]_n 25 A Rated voltage AC 440

V Size 26 x 100 mm Utilization category gL/gG Breaking Capacity 80 kA Usable for size/applications for SASIL fuse

switch Standard/Approval BS Shape cylindrical, offset-bolted tags Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 25 A Rated voltage 440 V Voltage type AC Rated switching capacity 80

kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No

ETIM for BXS25 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

440 V

Rated current (EF000227)

25 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BXS25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.