

INDUSTRIAL COMPONENT DATA

BXS80 EATON ELECTRIC Fuse-link, low voltage, 10 A, AC 440 V, 26 x 100 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: BXS80



Manufacturer	EATON - MOELLER
MPN / Reference	BXS80
Catalog number	10000
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-A7D2D368A0
Generated	2026-08-05

Product Overview

80AMP FUSE LINK FOR SASIL FUSE SWITCH

BXS80 - Fuse-link, low voltage, 80 A, AC 440 V, 26 x 100 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 80 A, AC 440 V, 26 x 100 mm, gL/gG, BS, cylindrical, offset-bolted tags, for SASIL fuse switch, Breaking Capacity 80 kA, Optional accessories, Supplied with

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 80 A, AC 440 V, 26 x 100 mm, gL/gG, BS Fuse, Fuse-link, low voltage, 80 A, AC 440 V, 26 x 100 mm, gL/gG, BS, cylindrical, offset-bolted tags, for SASIL fuse switch, Breaking Capacity 80 kA, Optional accessories, Supplied with

General specificationsProduct nameEaton Bussmann series low voltage British standard fusePart

no.BXS80EAN5027590493161Product Length/Depth27 millimetreProduct height27 millimetreProduct width78.5 millimetreProduct weight64.6 gramCompliancesCE

RoHSCertificationsBSProduct TradenameNoneProduct TypeLow voltage British standard fuseProduct Sub

TypeNoneElectrical dataAmperage Rating80 AVoltage rating440 VVoltage typeACBreaking capacity80 kAClassClass gG/gLProduct specificationsApplicationfor SASIL fuse switchFuse typeBXSCConnectionBolt-onTechnical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)Electric engineering, automation, process control

engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) ()

[BAB264011])Fuse construction type according to IEC 60269OtherType of currentACRated voltage AC440 VRated voltage

DCVRated current80 AUtilization categorygL/gG (cable protection/equipment protection)Breaking capacity80 kAColour
codeNoneType of fuse status indicatorNonePower loss at rated currentWMounting holesM10Centre-to-centre distance of
connections58 mm

ETIM for BXS80 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system accor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BXS80 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.