

INDUSTRIAL COMPONENT DATA

**C10M0-25 C10M0.25 CYLINDRICAL FUSE 10x38 0.25A AM
500V AC EATON ELECTRIC Fuse-link, 10x38 mm, 2A, gG**

Brand: EATON - MOELLER | Manufacturer Part Number: C10M0-25



Manufacturer	EATON - MOELLER
MPN / Reference	C10M0-25
Catalog number	CYLINDRICAL FUSE 10x38 0.25A AM 500V AC
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-4CDEF2035E
Generated	2026-08-06

Product Overview

Fuse-link, 10x38 mm, 2A, gG

cartridge fuse, BT, 0.25 A, AC 500 V, 10 x 38 mm, aM, IEC

CYLINDRICAL FUSE 10x38 0.25A AM 500V AC - Fuse-link, LV, 0.25 A, AC 500 V, 10 x 38 mm, aM, IEC

Fuse, fuse-link, low voltage, 0.25 A, AC 500 V, 10 x 38 mm, aM, IEC, cylindrical, motor protection, for industrial applications, IEC 60269-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product InformationFuse-link, LV, 0.25 A, AC 500 V, 10 x 38 mm, aM, IEC
Fuse, fuse-link, low voltage, 0.25 A, AC 500 V, 10 x 38 mm, aM, IEC, cylindrical, motor protection, for industrial applications, IEC 60269-2
Delivery programProduct range Fuse Basic function Fuse-link Field of application low voltage Rated current [I]_N 0.25 A Rated voltage AC 500

V Size 10 x 38 mm Utilization category aM Breaking Capacity 120 kA Suitable for size/applications motor protection

for industrial applications Standard/Approval IEC Shape cylindrical Standards/Regulations IEC 60269-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control

engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ()

[AFZ797013]) Size 10x38 mm Rated voltage 500 - 500 V Rated voltage Other Voltage type AC Utilization category aM

(switchgear protection) Rated operating frequency 45 - 62 Hz Nominal current 0.25 A With striker No Release

characteristic Other Breaking capacity 120 kA

ETIM for C10M0.25 Circuit breakers and fuses (EC002704)

Feature Name
Feature Value
Model (EF000010)
Ceramic fuse
Size (EF000088)
10x38 mm
Voltage type (EF000187)
AC
Rated current (EF000227)
0.25 A
Utilization category according to IEC 60269 (EF002572)
aM (switchgear protection)
Type of fuse status indicator (EF004473)
Other
Release characteristic (EF000889)
Other
Power loss at rated current (EF012389)
0.36 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C10M0-25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.