

INDUSTRIAL COMPONENT DATA

C22-D-G-K20 132430 EATON ELECTRIC C22-D-G-K20

Brand: EATON - MOELLER | Manufacturer Part Number: C22-D-G-K20



Manufacturer	EATON - MOELLER
MPN / Reference	C22-D-G-K20
Catalog number	132430
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-F6957210B4
Generated	2026-08-05

Product Overview

C22-D-G-K20

Pushbutton, Flat, momentary, 2 N/O, Screw connection, green, Blank, Bezel: titanium

Pushbutton, RMQ Compact, Complete unit, Design: Flat, momentary, Connection type: Screw connection, button plate: green, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 2 N/O, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Pushbutton, Flat, momentary, 2 N/O, Screw connection, green, Blank, Bezel: titanium Pushbutton, RMQ Compact, Complete unit, Design: Flat, momentary, Connection type: Screw connection, button plate: green, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 2 N/O, Standards: IEC/EN 60947-5-1, VDE 0660 Delivery program

Product range RMQ Compact Basic function Pushbutton actuators Single unit/Complete unit Complete unit Design Flat momentary Connection type Screw connection Button plate button plate green Button

plate Blank Name None Degree of Protection IP66, IP67, IP69 Front ring Bezel: titanium Connection to

SmartWire-DT no Contacts N/O = Normally open 2 N/O Contact sequence Contact travel? = Contact closed? = Contact open Contact diagram Technical data

General Standards IEC/EN 60947-5-1

VDE 0660 Lifespan, mechanical [Operations] > 5 x 10⁶ Operating frequency [Operations/h] ? 3600 Actuating force? 5

n Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP66, IP67, IP69 Ambient temperature Open-25 - +70 °C Ambient temperature Storage- -30 - + 80 °C Mounting position As required Terminal capacities Solid 2 x 0.5 - 1.5_x mm² Terminal capacities Flexible with ferrule 2 x 0.5 - 1.5_x mm² Tightening torque for terminal screw 0.8 Nm Contacts Rated impulse withstand voltage [U_{imp}] 4000 V AC Rated insulation voltage [U_i] 250 V Rated conditional short-circuit current [I_q] 1 kA Overvoltage category...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-D-G-K20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.