

## INDUSTRIAL COMPONENT DATA

# C22-D-S-K01-P3 181634 Y7-181634 EATON ELECTRIC

## Pushbutton, flat momentary black 1 N/C with cable 0.5m and M1..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-D-S-K01-P3



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | EATON - MOELLER       |
| MPN / Reference | C22-D-S-K01-P3        |
| Catalog number  | Y7-181634             |
| Category        | Push button, complete |
| Minimum order   | 1 Pcs                 |
| Document ID     | EO-45CC068C4E         |
| Generated       | 2026-08-03            |

### Product Overview

Pushbutton, flat; momentary; black; 1 N/C; with cable 0.5m and M12A plug

C22-D-S-K01-P3

Pushbutton, Flat, momentary, 1 NC, Cable (black) with M12A plug, 4 pole, 0.5 m, black, Blank, Bezel: titanium

Pushbutton, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with M12A plug, 4 pole, Cable Length: 0.5 m, button plate: black, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

### Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Pushbutton Catalog Number 181634 Model Code C22-D-S-K01-P3 EAN

4015081765010 Product Length/Depth 560 mm Product Height 30 mm Product Width 30 mm Product Weight 0.048 kg

Certifications CSA-C22.2 No. 14-05 and 94-M91

UL

CE

CSA File No.: 165628

IEC/EN 60947-5-1

CSA Class No.: 321103

UL Category Control No.: NKCR

UL 508

UL File No.: E29184

CSA

VDE 0660

CSA-C22.2 No. 14-18 and No. 94.2-15

CE marking Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1 Features & Functions

Bezel color Titanium Bezel material Plastic Design M12A

Flat

Classical Electric connection type Other Features Positive opening Fitted with: Front ring Inscription Blank General

Cable length 0.5 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with M12A plug, 4 pole Degree of protection NEMA 12

IP67/IP69K Lifespan, mechanical 5,000,000 Operations Mounting position As required Opening diameter 22.5 mm

Operating frequency 3600 Operations/h Overvoltage category III Pollution degree 3 Product category RMQ compact

solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resistance 30 g, Mechanical, Shock duration 11 ms

Tightening torque 2 Nm, Threaded ring

1 Nm, Plug Type Pushbutton actuator Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-D-S-K01-P3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.