

INDUSTRIAL COMPONENT DATA

C22-D-S-K01-P32 185654 EATON ELECTRIC Pushbutton, classic, flat, tasted, 1 N/C, black, cable (black) with m8..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-D-S-K01-P32



Manufacturer	EATON - MOELLER
MPN / Reference	C22-D-S-K01-P32
Catalog number	185654
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-8CA0F8B9F3
Generated	2026-08-04

Product Overview

Pushbutton, classic, flat, tasted, 1 N/C, black, cable (black) with m8 plug, 4 pole, 1 m
Push button flush compact, 22 mm; Return; Black; 1 NC; cable 1 m and connector M8
Pushbutton, Flat, momentary, 1 NC, Cable (black) with M8 plug, 4 pole, 1 m, black, Blank, Bezel: titanium
Pushbutton, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 1 m, button plate: black, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Pushbutton, Flat, momentary, 1 NC, Cable (black) with M8 plug, 4 pole, 1 m, black, Blank, Bezel: titanium
Pushbutton, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 1 m, button plate: black, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660
Delivery program

Product rangeRMQ compact solutionBasic functionPushbutton actuatorsSingle unit/Complete unitComplete unitDesignFlatmomentaryConnection typeCable (black) with M8 plug, 4 poleCable Length1 mButton platebutton plateblackButton plateBlankNameNoneDegree of ProtectionIP66, IP67, IP69 (front) IP65 (on rear)Front ringBezel: titaniumConnection to SmartWire-DTnoContactsN/C = Normally closed1 NCNotes= safety function, by positive opening to IEC/EN 60947-5-1Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1[mm]4.65Maximum travel [mm]5.7Minimum force for positive opening [N]15Contact sequenceContact travel? = Contact closed? = Contact openContact diagramPositive opening (ZW)yesTechnical data GeneralStandardsIEC/EN 60947-5-1....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-D-S-K01-P32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.