

INDUSTRIAL COMPONENT DATA

C22-D-S-K11 132438 EATON ELECTRIC C22-D-S-K11

Brand: EATON - MOELLER | Manufacturer Part Number: C22-D-S-K11



Manufacturer	EATON - MOELLER
MPN / Reference	C22-D-S-K11
Catalog number	132438
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-C16D04A343
Generated	2026-08-06

Product Overview

C22-D-S-K11

Pushbutton, Flat, momentary, 1 NC, 1 N/O, Screw connection, black, Blank, Bezel: titanium

Pushbutton, RMQ Compact, Complete unit, Design: Flat, momentary, Connection type: Screw connection, button plate: black, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, N/O = Normally open: 1 N/O, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 20, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Pushbutton, Flat, momentary, 1 NC, 1 N/O, Screw connection, black, Blank, Bezel: titaniumPushbutton, RMQ Compact, Complete unit, Design: Flat, momentary, Connection type: Screw connection, button plate: black, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, N/O = Normally open: 1 N/O, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 20, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660Delivery program Product rangeRMQ CompactBasic functionPushbutton actuatorsSingle unit/Complete unitComplete unitDesignFlatmomentaryConnection typeScrew connectionButton platebutton plateblackButton plateBlankNameNoneDegree of ProtectionIP66, IP67, IP69Front ringBezel: titaniumConnection to

SmartWire-DTnoContactsN/C = Normally closed1 NCN/O = Normally open1 N/ONotes= safety function, by positive opening to IEC/EN 60947-5-1Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1[mm]4.65Maximum travel [mm]5.7Minimum force for positive opening [N]20Contact sequenceContact travel? = Contact closed? = Contact openContact diagramPositive opening (ZW)yesTechnical data
GeneralStandardsIEC/EN 60947-5-1
VDE 0660Lifespan, mechanical [Operations]> 5 x 106Operating frequency [Operations/h]? 3600Actuating...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-D-S-K11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.