

INDUSTRIAL COMPONENT DATA

C22-D-X-K01-P65 185620 Y7-185620 EATON ELECTRIC Pushbutton, classic, flat, tasted, 1 N/C, cable (black) with..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-D-X-K01-P65



Manufacturer	EATON - MOELLER
MPN / Reference	C22-D-X-K01-P65
Catalog number	Y7-185620
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-DE5673FCD4
Generated	2026-08-04

Product Overview

Pushbutton, classic, flat, tasted, 1 N/C, cable (black) with non-terminated end, 4 pole, 3.5 m

C22-D-X-K01-P65

Pushbutton, Flat, momentary, 1 NC, Cable (black) with non-terminated end, 4 pole, 3.5 m, Without button plate, Bezel: titanium

Pushbutton, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, button plate: Without button plate, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Pushbutton, Flat, momentary, 1 NC, Cable (black) with non-terminated end, 4 pole, 3.5 m, Without button plate, Bezel: titanium
Pushbutton, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, button plate: Without button plate, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening

(ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

General specificationsProduct nameEaton Moeller® series C22 PushbuttonPart

no.C22-D-X-K01-P65EAN4015081811144Product Length/Depth3560 millimetreProduct height30 millimetreProduct width30 millimetreProduct weight0.122 kilogramCertificationsCE

UL

VDE 0660

IEC/EN 60947-5-1

CSA

CE marking

UL Category Control No.: NKCR

UL File No.: E29184

CSA File No.: 165628

CSA Class No.: 321103

CSA-C22.2 No. 14-18 and No. 94.2-15

UL 508Product TradenameC22Product TypePushbuttonProduct Sub TypeNoneCatalog NotesContacts with safety function, by positive opening to IEC/EN 60947-5-1Features & FunctionsBezel colorTitaniumBezel materialPlasticDesignFlat

ClassicalElectric connection typeCableFeaturesPositive openingFitted with:Front ringGeneral informatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-D-X-K01-P65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.