

INDUSTRIAL COMPONENT DATA

C22-D-X-K10 132469 EATON ELECTRIC C22-D-X-K10

Brand: EATON - MOELLER | Manufacturer Part Number: C22-D-X-K10



Manufacturer	EATON - MOELLER
MPN / Reference	C22-D-X-K10
Catalog number	132469
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-B025F46540
Generated	2026-08-05

Product Overview

C22-D-X-K10

Pushbutton, Flat, momentary, 1 N/O, Screw connection, Without button plate, Bezel: titanium

Pushbutton, RMQ Compact, Complete unit, Design: Flat, momentary, Connection type: Screw connection, button plate: Without button plate, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Pushbutton, Flat, momentary, 1 N/O, Screw connection, Without button plate, Bezel: titaniumPushbutton, RMQ Compact, Complete unit, Design: Flat, momentary, Connection type: Screw connection, button plate: Without button plate, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660Delivery program

Product rangeRMQ CompactBasic functionPushbutton actuatorsSingle unit/Complete unitComplete unitDesignFlatmomentaryConnection typeScrew connectionButton platebutton plateWithout button plateDegree of ProtectionIP66, IP67, IP69Front ringBezel: titaniumConnection to SmartWire-DTnoContactsN/O = Normally open1 N/OContact sequenceContact travel? = Contact closed? = Contact openContact diagramTechnical data GeneralStandardsIEC/EN 60947-5-1

VDE 0660Lifespan, mechanical [Operations]> 5 x 106Operating frequency [Operations/h]? 3600Actuating force? 5 nClimatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP66, IP67, IP69Ambient temperatureOpen-25 - +70 °CAmbient

temperatureStorage- -30 - + 80 °C
Mounting positionAs required
Terminal capacitiesSolid2 x 0.5 - 1.5_x mm²
Terminal capacitiesFlexible with ferrule2 x 0.5 - 1.5_x mm²
Tightening torque for terminal screw0.8 Nm
ContactsRated impulse withstand voltage [U_{imp}]4000 V AC
Rated insulation voltage [U_i]250 V
Rated conditional short-circuit current [I_q]1 kA
Overvoltage category/pollution degreeII...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-D-X-K10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.