

## INDUSTRIAL COMPONENT DATA

# C22-D-X-K11-P65 185623 Y7-185623 EATON ELECTRIC

## Pushbutton, classic, flat, tasted, 1 N/C, 1 N/O, cable (blac..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-D-X-K11-P65



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | EATON - MOELLER       |
| MPN / Reference | C22-D-X-K11-P65       |
| Catalog number  | Y7-185623             |
| Category        | Push button, complete |
| Minimum order   | 1 unit                |
| Document ID     | EO-8B6243236D         |
| Generated       | 2026-08-02            |

### Product Overview

Pushbutton, classic, flat, tasted, 1 N/C, 1 N/O, cable (black) with non-terminated end, 4 pole, 3.5 m

C22-D-X-K11-P65

Eaton Moeller® series C22 Pushbutton, Flat, momentary, 1 NC, 1 N/O, Cable (black) with non-terminated end, 4 pole, 3.5 m, Without button plate, Bezel: titanium

Pushbutton, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, button plate: Without button plate, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, N/O = Normally open: 1 N/O, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 20, Positive opening (ZW): yes , Standards: IEC/EN 60947-5-1, VDE 0660

## STRUCTURED PRODUCT DATA

### Technical Specifications

| TECHNICAL ATTRIBUTE                    | VALUE                |
|----------------------------------------|----------------------|
| Number of command positions (EF001372) | 1                    |
| Type of button (EF001546)              | Flat                 |
| Colour button (EF000190)               | Without button plate |
| Transparent (EF006243)                 | No                   |
| Construction type lens (EF006253)      | Round                |
| Hole diameter (EF000079)               | 22.5 mm              |
| Width opening (EF004565)               | 0 mm                 |
| Height opening (EF004778)              | 0 mm                 |

**CONTINUED**

## Technical Specifications

| TECHNICAL ATTRIBUTE                                      | VALUE      |
|----------------------------------------------------------|------------|
| Suitable for lighting (EF001142)                         | No         |
| Switching function latching (EF007447)                   | No         |
| Spring-return (EF001407)                                 | Yes        |
| Supply voltage lamp (EF006522)                           | 0 V        |
| Number of contacts as normally open contact (EF008256)   | 1          |
| Number of contacts as normally closed contact (EF008255) | 1          |
| Number of contacts as change-over contact (EF008257)     | 0          |
| Type of electric connection (EF003961)                   | Cable      |
| With front ring (EF006014)                               | Yes        |
| Material front ring (EF005972)                           | Plastic    |
| Colour front ring (EF002429)                             | Titanium   |
| Degree of protection (IP) (EF005474)                     | IP67/IP69K |
| Degree of protection (NEMA) (EF011959)                   | 12         |

## Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

## Additional Product Information

### General specifications

Product Name Eaton Moeller® series C22 Pushbutton Catalog Number 185623 Model Code C22-D-X-K11-P65 EAN 4015081811175 Product Length/Depth 3560 mm Product Height 30 mm Product Width 30 mm Product Weight 0.122 kg

Certifications UL

IEC/EN 60947-5-1

VDE 0660

CSA

CE

CSA Class No.: 321103

CSA File No.: 165628

UL 508

CSA-C22.2 No. 14-18 and No. 94.2-15

CE marking

UL Category Control No.: NKCR

UL File No.: E29184 Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1 Features & Functions

Bezel color Titanium Bezel material Plastic Design Flat

Classical Electric connection type Cable Features Positive opening Fitted with: Front ring General

Cable length 3.5 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with

non-terminated end, 4 pole Degree of protection NEMA 12

IP67/IP69K Mounting position As required Opening diameter 22.5 mm Operating frequency 3600 Operations/h Overvoltage category III Pollution degree 3 Product category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resista...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-D-X-K11-P65 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.