

INDUSTRIAL COMPONENT DATA

C22-D-X-K11-P65 185623 Y7-185623 EATON ELECTRIC

Pushbutton, classic, flat, tasted, 1 N/C, 1 N/O, cable (blac..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-D-X-K11-P65



Manufacturer	EATON - MOELLER
MPN / Reference	C22-D-X-K11-P65
Catalog number	Y7-185623
Category	Push button, complete
Minimum order	1 unit
Document ID	EO-8B6243236D
Generated	2026-08-04

Product Overview

Pushbutton, classic, flat, tasted, 1 N/C, 1 N/O, cable (black) with non-terminated end, 4 pole, 3.5 m

C22-D-X-K11-P65

Eaton Moeller® series C22 Pushbutton, Flat, momentary, 1 NC, 1 N/O, Cable (black) with non-terminated end, 4 pole, 3.5 m, Without button plate, Bezel: titanium

Pushbutton, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, button plate: Without button plate, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, N/O = Normally open: 1 N/O, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 20, Positive opening (ZW): yes , Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Number of command positions (EF001372)	1
Type of button (EF001546)	Flat
Colour button (EF000190)	Without button plate
Transparent (EF006243)	No
Construction type lens (EF006253)	Round
Hole diameter (EF000079)	22.5 mm
Width opening (EF004565)	0 mm
Height opening (EF004778)	0 mm

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Suitable for lighting (EF001142)	No
Switching function latching (EF007447)	No
Spring-return (EF001407)	Yes
Supply voltage lamp (EF006522)	0 V
Number of contacts as normally open contact (EF008256)	1
Number of contacts as normally closed contact (EF008255)	1
Number of contacts as change-over contact (EF008257)	0
Type of electric connection (EF003961)	Cable
With front ring (EF006014)	Yes
Material front ring (EF005972)	Plastic
Colour front ring (EF002429)	Titanium
Degree of protection (IP) (EF005474)	IP67/IP69K
Degree of protection (NEMA) (EF011959)	12

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Pushbutton Catalog Number 185623 Model Code C22-D-X-K11-P65 EAN 4015081811175 Product Length/Depth 3560 mm Product Height 30 mm Product Width 30 mm Product Weight 0.122 kg

Certifications UL

IEC/EN 60947-5-1

VDE 0660

CSA

CE

CSA Class No.: 321103

CSA File No.: 165628

UL 508

CSA-C22.2 No. 14-18 and No. 94.2-15

CE marking

UL Category Control No.: NKCR

UL File No.: E29184 Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1 Features & Functions

Bezel color Titanium Bezel material Plastic Design Flat

Classical Electric connection type Cable Features Positive opening Fitted with: Front ring General

Cable length 3.5 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with

non-terminated end, 4 pole Degree of protection NEMA 12

IP67/IP69K Mounting position As required Opening diameter 22.5 mm Operating frequency 3600 Operations/h Overvoltage category III Pollution degree 3 Product category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resista...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-D-X-K11-P65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.